




P = 0.03 кВт




50 Гц			i	Тип	m , кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
11.5	21	6.5	120.3	BK10Z-../D04LA4	21	7000	-	13.5	18	7.6
9.5	25	6.5	143.2	"	"	7000	-	11.5	20.5	8.0
8.0	29.5	6.8	170.6	"	"	7000	-	9.5	25	8.0
6.6	35.5	5.6	204.7	"	"	7000	-	8.0	29	6.9
5.3	44	4.5	257.9	"	"	7000	-	6.3	37	5.4
4.5	51	3.6	302.4	"	"	7000	-	5.4	42.5	4.3
3.7	62	2.7	373.4	"	"	7000	-	4.4	52	3.2
3.2	71	2.1	428.8	"	"	7000	-	3.8	60	2.5
2.5	66	3.3	552.3	BK10G06-../D04LA4	25	7000	-	3.0	51	4.3
2.2	77	2.9	635.5	"	"	7000	-	2.6	62	3.5
1.8	98	2.2	789.7	"	"	7000	-	2.1	80	2.8
1.5	118	1.85	929.3	"	"	7000	-	1.8	94	2.3
1.3	139	1.6	1112	"	"	7000	-	1.5	116	1.9
1.0	184	1.2	1361	"	"	7000	-	1.2	149	1.5
0.7	220*	1.0	1971	"	"	7000	-	0.85	220*	1.0
0.6	220*	1.0	2261	"	"	7000	-	0.75	220*	1.0
0.48	220*	1.0	2849	"	"	7000	-	0.6	220*	1.0
0.39	220*	1.0	3537	"	"	7000	-	0.46	220*	1.0
0.33	220*	1.0	4120	"	"	7000	-	0.4	220*	1.0
1.6	110	3.3	891.2	BK20G06-../D04LA4	34	8700	9000	1.9	88	4.1
1.3	138	2.6	1066	"	"	8700	9000	1.6	108	3.3
1.1	165	2.2	1305	"	"	8700	9000	1.3	135	2.7
0.95	193	1.85	1424	"	"	8700	9000	1.2	149	2.4
0.85	220	1.65	1650	"	"	8700	9000	1.0	183	1.95
0.7	270	1.35	2062	"	"	8700	9000	0.8	235	1.55
0.6	320	1.15	2366	"	"	8700	9000	0.7	270	1.35
0.48	360*	1.0	2831	"	"	8700	9000	0.6	360*	1.0
0.39	360*	1.0	3515	"	"	8700	9000	0.47	360*	1.0
0.33	360*	1.0	4094	"	"	8700	9000	0.4	360*	1.0
1.2	150	3.3	1142	BK30G06-../D04LA4	40	11200	12000	1.5	116	4.2
0.85	220	2.2	1620	"	"	11200	12000	1.0	183	2.7
0.7	270	1.8	2024	"	"	11200	12000	0.85	220	2.2
0.55	350	1.4	2533	"	"	11200	12000	0.65	295	1.65
0.46	415	1.2	2986	"	"	11200	12000	0.55	345	1.4
0.4	480	1.0	3399	"	"	11200	12000	0.48	400	1.25
0.35	490*	1.0	3959	"	"	11200	12000	0.41	490*	1.0

P = 0.04 кВт

11.5	28	4.9	120.3	BK10Z-../D04LA4	21	7000	-	13.5	24	5.7
9.5	33.5	4.9	143.2	"	"	7000	-	11.5	27.5	5.9
8.0	39.5	5.1	170.6	"	"	7000	-	9.5	33	6.1
6.6	47	4.3	204.7	"	"	7000	-	8.0	39	5.1
5.3	59	3.4	257.9	"	"	7000	-	6.3	49.5	4.0
4.5	68	2.7	302.4	"	"	7000	-	5.4	57	3.2
3.7	83	2.0	373.4	"	"	7000	-	4.4	70	2.4
3.2	95	1.55	428.8	"	"	7000	-	3.8	80	1.85
3.0	78	2.8	459.2	BK10G06-../D04LA4	25	7000	-	3.6	62	3.5
2.5	96	2.3	552.3	"	"	7000	-	3.0	77	2.9
2.2	112	1.95	635.5	"	"	7000	-	2.6	91	2.4
1.8	140	1.55	789.7	"	"	7000	-	2.1	116	1.9
1.5	167	1.3	929.3	"	"	7000	-	1.8	135	1.65
1.3	195	1.15	1112	"	"	7000	-	1.5	165	1.35
1.0	255	0.86	1361	"	"	7000	-	1.2	210	1.05
2.2	110	3.3	630.0	BK20G06-../D04LA4	34	8700	9000	2.6	89	4.0
1.8	138	2.6	757.0	"	"	8700	9000	2.2	109	3.3
1.6	156	2.3	891.2	"	"	8700	9000	1.9	128	2.8

P = 0.04 кВт




Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
1.3	195	1.85	1066	BK20G06-.../D04LA4	34	8700	9000	1.6	155	2.3
1.1	230	1.55	1305	"	"	8700	9000	1.3	192	1.9
0.95	270	1.35	1424	"	"	8700	9000	1.2	210	1.7
0.85	305	1.2	1650	"	"	8700	9000	1.0	255	1.4
0.7	360*	1.0	2062	"	"	8700	9000	0.8	360*	1.0
0.6	360*	1.0	2366	"	"	8700	9000	0.7	360*	1.0
1.7	147	3.3	810.9	BK30G06-.../D04LA4	40	11200	12000	2.0	122	4.0
1.5	167	2.9	954.1	"	"	11200	12000	1.7	143	3.4
1.2	210	2.3	1142	"	"	11200	12000	1.5	165	3.0
0.85	305	1.6	1620	"	"	11200	12000	1.0	255	1.9
0.7	375	1.3	2024	"	"	11200	12000	0.85	305	1.6
0.55	480	1.0	2533	"	"	11200	12000	0.65	405	1.2
0.46	490*	1.0	2986	"	"	11200	12000	0.55	490*	1.0

P = 0.06 кВт

22	23	8.7	61.68	BK10-.../D06LA4	23	7000	-	26.5	19.2	10
19	26.5	7.5	72.31	"	"	7000	-	22.5	22	9.1
15.5	32	5.6	89.30	"	"	7000	-	18.5	26.5	6.7
13.5	36	4.4	102.5	"	"	7000	-	16	30	5.2
11.5	42	3.3	120.3	BK10Z-.../D06LA4	25	7000	-	13.5	36	3.8
9.5	50	3.3	143.2	"	"	7000	-	11.5	41.5	3.9
8.0	59	3.4	170.6	"	"	7000	-	9.5	50	4.0
6.6	71	2.8	204.7	"	"	7000	-	8.0	58	3.4
5.3	88	2.3	257.9	"	"	7000	-	6.3	74	2.7
4.5	103	1.8	302.4	"	"	7000	-	5.4	85	2.2
3.7	125	1.3	373.4	"	"	7000	-	4.4	105	1.55
3.2	143	1.05	428.8	"	"	7000	-	3.8	120	1.25
3.0	129	1.7	459.2	BK10G06-.../D06LA4	28	7000	-	3.6	104	2.1
2.5	157	1.4	552.3	"	"	7000	-	3.0	127	1.75
2.2	180	1.2	635.5	"	"	7000	-	2.6	149	1.5
1.8	220	1.0	789.7	"	"	7000	-	2.1	187	1.2
1.5	265	0.83	929.3	"	"	7000	-	1.8	215	1.0
4.6	100	3.1	298.2	BK20Z-.../D06LA4	34	8700	9000	5.5	84	3.7
3.7	123	2.4	367.7	"	"	8700	9000	4.5	101	2.9
3.2	120	3.0	429.7	BK20G06-.../D06LA4	38	8700	9000	3.8	98	3.7
2.6	149	2.4	524.5	"	"	8700	9000	3.1	122	3.0
2.2	178	2.0	630.0	"	"	8700	9000	2.6	148	2.4
1.8	220	1.65	757.0	"	"	8700	9000	2.2	178	2.0
1.6	245	1.45	891.2	"	"	8700	9000	1.9	205	1.75
1.3	305	1.2	1066	"	"	8700	9000	1.6	245	1.45
1.1	360	1.0	1305	"	"	8700	9000	1.3	305	1.2
0.95	360*	1.0	1424	"	"	8700	9000	1.2	360*	1.0
3.6	128	3.1	380.7	BK30Z-.../D06LA4	41	11200	12000	4.3	107	3.8
3.1	147	2.6	441.3	"	"	11200	12000	3.7	123	3.1
2.4	163	3.0	567.0	BK30G06-.../D06LA4	44	11200	12000	2.9	132	3.7
2.1	188	2.6	652.5	"	"	11200	12000	2.5	155	3.2
1.7	235	2.1	810.9	"	"	11200	12000	2.0	196	2.5
1.5	265	1.85	954.1	"	"	11200	12000	1.7	230	2.1
1.2	330	1.5	1142	"	"	11200	12000	1.5	260	1.9
0.85	475	1.05	1620	"	"	11200	12000	1.0	400	1.25
0.7	490*	1.0	2024	"	"	11200	12000	0.85	490*	1.0
1.2	290	2.9	1189	BK40G10-.../D06LA4	68	11700	17000	1.4	240	3.5
0.95	380	2.2	1428	"	"	11700	17000	1.2	290	2.9
0.8	465	1.85	1798	"	"	11700	17000	0.95	385	2.2
0.65	580	1.45	2108	"	"	11700	17000	0.8	465	1.85




P = 0.06 кВт

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
0.55	700	1.2	2604	BK40G10-.../D06LA4	68	11700	17000	0.65	580	1.45
0.44	850*	1.0	3077	"	"	11700	17000	0.55	850*	1.0
0.36	850*	1.0	3800	"	"	11700	17000	0.43	850*	1.0
1.0	370	3.1	1398	BK50G10-.../D06LA4	97	14100	26000	1.2	300	3.8
0.75	510	2.3	1816	"	"	14100	26000	0.9	415	2.8
0.6	630	1.85	2450	"	"	14100	26000	0.7	530	2.2
0.5	760	1.5	2730	"	"	14100	26000	0.6	620	1.85
0.39	960	1.2	3492	"	"	14100	26000	0.47	790	1.45
0.35	1080	1.05	3870	"	"	14100	26000	0.42	890	1.3
0.31	1150*	1.0	4443	"	"	14100	26000	0.37	1150*	1.0
0.39	920	2.7	3533	BK60G20-.../D06LA4	123	16600	34000	0.46	690	3.6
0.32	1240	2.0	4239	"	"	16600	34000	0.39	920	2.7
0.27	1570	1.6	5072	"	"	16600	34000	0.32	1240	2.0
0.24	1830	1.35	5721	"	"	16600	34000	0.29	1420	1.75
0.21	2150	1.15	6565	"	"	16600	34000	0.25	1740	1.45
0.17	2500*	1.0	8093	"	"	16600	34000	0.21	2500*	1.0
0.16	2500*	1.0	8990	"	"	16600	34000	0.19	2500*	1.0
0.21	2000	2.9	6504	BK70G20-.../D06LA4	201	24100	50000	0.25	1580	3.6
0.17	2650	2.2	8149	"	"	24100	50000	0.2	2150	2.7
0.15	3100	1.85	9351	"	"	24100	50000	0.18	2450	2.3
0.12	4050	1.4	11529	"	"	24100	50000	0.15	3100	1.85

P = 0.09 кВт

39.5	19.5	10	34.25	BK10-.../D06LA4	23	5600	-	47.5	16.2	12
33.5	23	8.7	40.79	"	"	6000	-	40	19.3	10
28	27	7.4	48.96	"	"	6400	-	33.5	22.5	8.9
22	34.5	5.8	61.68	"	"	7000	-	26.5	28.5	7.0
19	39.5	5.1	72.31	"	"	7000	-	22.5	33.5	6.0
15.5	48	3.7	89.30	"	"	7000	-	18.5	40	4.5
13.5	54	2.9	102.5	"	"	7000	-	16	45.5	3.5
11.5	63	2.2	120.3	BK10Z-.../D06LA4	25	7000	-	13.5	54	2.5
9.5	75	2.2	143.2	"	"	7000	-	11.5	62	2.6
8.0	89	2.2	170.6	"	"	7000	-	9.5	75	2.7
6.6	106	1.9	204.7	"	"	7000	-	8.0	88	2.3
5.3	132	1.5	257.9	"	"	7000	-	6.3	111	1.8
4.5	154	1.2	302.4	"	"	7000	-	5.4	128	1.45
3.7	188	0.88	373.4	"	"	7000	-	4.4	158	1.05
3.3	186	1.2	410.8	BK10G06-.../D06LA4	28	7000	-	4.0	151	1.45
2.7	225	0.98	501.4	"	"	7000	-	3.3	184	1.2
2.5	245	0.9	552.3	"	"	7000	-	3.0	200	1.1
6.6	106	3.1	207.5	BK20Z-.../D06LA4	34	8700	9000	7.9	89	3.7
5.2	135	2.4	259.9	"	"	8700	9000	6.3	111	3.0
4.6	151	2.1	298.2	"	"	8700	9000	5.5	126	2.5
3.7	185	1.6	367.7	"	"	8700	9000	4.5	152	1.9
3.2	192	1.9	429.7	BK20G06-.../D06LA4	38	8700	9000	3.8	159	2.3
2.6	235	1.55	524.5	"	"	8700	9000	3.1	196	1.85
2.2	280	1.3	630.0	"	"	8700	9000	2.6	235	1.55
1.8	345	1.05	757.0	"	"	8700	9000	2.2	280	1.3
1.6	385	0.94	891.2	"	"	8700	9000	1.9	320	1.15
4.4	160	2.4	308.3	BK30Z-.../D06LA4	41	11200	12000	5.3	132	2.9
3.6	193	2.1	380.7	"	"	11200	12000	4.3	161	2.5
3.1	220	1.75	441.3	"	"	11200	12000	3.7	185	2.1
2.9	210	2.3	471.5	BK30G06-.../D06LA4	44	11200	12000	3.5	173	2.8
2.4	255	1.9	567.0	"	"	11200	12000	2.9	210	2.3

P = 0.09 кВт




50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
2.1	295	1.65	652.5	BK30G06-.../D06LA4	44	11200	12000	2.5	245	2.0
1.7	365	1.35	810.9	"	"	11200	12000	2.0	305	1.6
1.5	410	1.2	954.1	"	"	11200	12000	1.7	360	1.35
1.2	510	0.96	1142	"	"	11200	12000	1.5	410	1.2
1.1	560	0.88	1281	"	"	11200	12000	1.3	470	1.05
3.9	178	3.3	348.7	BK40Z-.../D06LA4	64	11700	17000	4.7	148	3.9
3.2	210	2.7	430.0	"	"	11700	17000	3.8	180	3.2
1.8	295	2.9	756.7	BK40G10-.../D06LA4	68	11700	17000	2.2	230	3.7
1.4	400	2.1	998.3	"	"	11700	17000	1.7	320	2.7
1.2	475	1.8	1189	"	"	11700	17000	1.4	395	2.2
0.95	610	1.4	1428	"	"	11700	17000	1.2	475	1.8
0.8	730	1.15	1798	"	"	11700	17000	0.95	610	1.4
0.65	850*	1.0	2108	"	"	11700	17000	0.8	850*	1.0
0.6	850*	1.0	2350	"	"	11700	17000	0.7	850*	1.0
1.6	350	3.3	859.8	BK50G10-.../D06LA4	97	14100	26000	1.9	285	4.0
1.4	410	2.8	1024	"	"	14100	26000	1.6	350	3.3
1.1	530	2.2	1230	"	"	14100	26000	1.4	410	2.8
0.9	660	1.75	1549	"	"	14100	26000	1.1	530	2.2
0.75	790	1.45	1816	"	"	14100	26000	0.9	650	1.75
0.6	980	1.15	2450	"	"	14100	26000	0.7	830	1.4
0.5	1150*	1.0	2730	"	"	14100	26000	0.6	1150*	1.0
0.45	1150*	1.0	3025	"	"	14100	26000	0.55	1150*	1.0
0.7	750	3.3	2010	BK60G20-.../D06LA4	123	16600	34000	0.85	530	4.7
0.6	930	2.7	2371	"	"	16600	34000	0.7	720	3.5
0.5	1180	2.1	2733	"	"	16600	34000	0.6	890	2.8
0.39	1650	1.5	3533	"	"	16600	34000	0.46	1320	1.9
0.32	2100	1.2	4239	"	"	16600	34000	0.39	1650	1.5
0.27	2500*	1.0	5072	"	"	16600	34000	0.32	2500*	1.0
0.24	2500*	1.0	5721	"	"	16600	34000	0.29	2500*	1.0
0.35	1750	3.3	3894	BK70G20-.../D06LA4	201	24100	50000	0.42	1340	4.3
0.3	2150	2.7	4531	"	"	24100	50000	0.36	1680	3.4
0.25	2700	2.1	5436	"	"	24100	50000	0.3	2150	2.7
0.21	3350	1.7	6504	"	"	24100	50000	0.25	2700	2.1
0.17	4350	1.3	8149	"	"	24100	50000	0.2	3550	1.6
0.15	5000	1.15	9351	"	"	24100	50000	0.18	4050	1.4
0.12	5700*	1.0	11529	"	"	24100	50000	0.15	5700*	1.0

P = 0.12 кВт


47	21.5	9.3	28.76	BK10-.../D06LA4	23	5200	-	57	18	11
39.5	26	7.7	34.25	"	"	5600	-	47.5	21.5	9.3
33.5	30.5	6.6	40.79	"	"	6000	-	40	25.5	7.8
28	36	5.6	48.96	"	"	6400	-	33.5	30	6.7
22	46	4.3	61.68	"	"	7000	-	26.5	38	5.3
19	53	3.8	72.31	"	"	7000	-	22.5	44.5	4.5
15.5	64	2.8	89.30	"	"	7000	-	18.5	53	3.4
13.5	72	2.2	102.5	"	"	7000	-	16	60	2.6
11.5	84	1.65	120.3	BK10Z-.../D06LA4	25	7000	-	13.5	72	1.9
9.5	101	1.6	143.2	"	"	7000	-	11.5	83	1.95
8.0	118	1.7	170.6	"	"	7000	-	9.5	100	2.0
6.6	142	1.4	204.7	"	"	7000	-	8.0	117	1.7
5.3	177	1.15	257.9	"	"	7000	-	6.3	149	1.35
4.5	205	0.9	302.4	"	"	7000	-	5.4	171	1.15
4.0	210	1.05	343.2	BK10G06-.../D06LA4	28	7000	-	4.8	173	1.25
3.3	255	0.86	410.8	"	"	7000	-	4.0	205	1.05

P = 0.12 кВт



50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
14	70	3.3	96.99	BK20Z-../D06LA4	34	8700	9000	17	57	4.1
11	88	3.8	124.2	"	"	8700	9000	13.5	72	4.6
9.4	102	3.2	144.5	"	"	8700	9000	11.5	83	4.0
7.8	121	2.7	173.4	"	"	8700	9000	9.4	101	3.3
6.6	142	2.3	207.5	"	"	8700	9000	7.9	118	2.8
5.2	180	1.85	259.9	"	"	8700	9000	6.3	149	2.2
4.6	200	1.55	298.2	"	"	8700	9000	5.5	168	1.85
3.7	245	1.2	367.7	"	"	8700	9000	4.5	200	1.45
3.2	260	1.4	429.7	BK20G06-../D06LA4	38	8700	9000	3.8	215	1.65
2.6	320	1.15	524.5	"	"	8700	9000	3.1	265	1.35
2.2	380	0.95	630.0	"	"	8700	9000	2.6	320	1.15
6.3	149	3.0	216.5	BK30Z-../D06LA4	41	11200	12000	7.5	125	3.6
5.3	177	2.5	255.3	"	"	11200	12000	6.4	146	3.1
4.4	210	1.85	308.3	"	"	11200	12000	5.3	177	2.2
3.6	255	1.6	380.7	"	"	11200	12000	4.3	215	1.85
3.1	295	1.3	441.3	"	"	11200	12000	3.7	245	1.55
2.9	290	1.7	471.5	BK30G06-../D06LA4	44	11200	12000	3.5	235	2.1
2.4	350	1.4	567.0	"	"	11200	12000	2.9	285	1.7
2.1	400	1.25	652.5	"	"	11200	12000	2.5	335	1.45
1.7	495	0.99	810.9	"	"	11200	12000	2.0	420	1.15
1.5	560	0.88	954.1	"	"	11200	12000	1.7	490	1.0
3.9	235	2.5	348.7	BK40Z-../D06LA4	64	11700	17000	4.7	197	2.9
3.2	285	2.0	430.0	"	"	11700	17000	3.8	240	2.4
2.8	255	3.3	487.3	BK40G10-../D06LA4	68	11700	17000	3.4	200	4.3
2.5	290	2.9	540.0	"	"	11700	17000	3.0	230	3.7
2.1	355	2.4	660.2	"	"	11700	17000	2.5	285	3.0
1.8	420	2.0	756.7	"	"	11700	17000	2.2	330	2.6
1.4	550	1.55	998.3	"	"	11700	17000	1.7	450	1.9
1.2	660	1.3	1189	"	"	11700	17000	1.4	550	1.55
0.95	840	1.0	1428	"	"	11700	17000	1.2	660	1.3
0.8	850*	1.0	1798	"	"	11700	17000	0.95	850*	1.0
3.3	275	3.1	414.8	BK50Z-../D06LA4	93	14100	26000	4.0	225	3.8
2.1	360	3.2	651.7	BK50G10-../D06LA4	97	14100	26000	2.5	295	3.9
1.6	490	2.3	859.8	"	"	14100	26000	1.9	405	2.8
1.4	560	2.1	1024	"	"	14100	26000	1.6	490	2.3
1.1	730	1.6	1230	"	"	14100	26000	1.4	570	2.0
0.9	900	1.3	1549	"	"	14100	26000	1.1	730	1.6
0.75	1080	1.05	1816	"	"	14100	26000	0.9	900	1.3
0.6	1150*	1.0	2450	"	"	14100	26000	0.7	1150*	1.0
0.85	930	2.7	1618	BK60G20-../D06LA4	123	16600	34000	1.1	630	4.0
0.75	1070	2.3	1810	"	"	16600	34000	0.9	810	3.1
0.6	1400	1.8	2371	"	"	16600	34000	0.7	1130	2.2
0.5	1750	1.45	2733	"	"	16600	34000	0.6	1370	1.8
0.39	2350	1.05	3533	"	"	16600	34000	0.46	1940	1.3
0.32	2500*	1.0	4239	"	"	16600	34000	0.39	2500*	1.0
0.45	1900	3.0	3041	BK70G20-../D06LA4	201	24100	50000	0.55	1440	4.0
0.39	2250	2.5	3505	"	"	24100	50000	0.47	1750	3.3
0.35	2550	2.2	3894	"	"	24100	50000	0.42	2000	2.9
0.3	3100	1.85	4531	"	"	24100	50000	0.36	2450	2.3
0.25	3850	1.5	5436	"	"	24100	50000	0.3	3100	1.85
0.21	4750	1.2	6504	"	"	24100	50000	0.25	3850	1.5
0.17	5700*	1.0	8149	"	"	24100	50000	0.2	5700*	1.0
0.15	5700*	1.0	9351	"	"	24100	50000	0.18	5700*	1.0


P = 0.18 кВт



50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
114	13.8	8.3	11.93	BK10-../D06LA4	23	3100	-	136	11.6	9.9
80	19.3	7.0	16.92	"	"	3700	-	96	16.1	8.4
73	21	9.5	18.52	"	"	4300	-	88	17.5	11
60	25.5	7.8	22.65	"	"	4650	-	72	21	9.5
47	32.5	6.2	28.76	"	"	5200	-	57	27	7.4
39.5	39	5.1	34.25	"	"	5600	-	47.5	32.5	6.2
33.5	46	4.3	40.79	"	"	6000	-	40	38.5	5.2
28	54	3.7	48.96	"	"	6400	-	33.5	45.5	4.4
22	69	2.9	61.68	"	"	7000	-	26.5	57	3.5
19	79	2.5	72.31	"	"	7000	-	22.5	67	3.0
15.5	96	1.85	89.30	"	"	7000	-	18.5	80	2.2
13.5	108	1.45	102.5	"	"	7000	-	16	91	1.75
11.5	127	1.1	120.3	BK10Z-../D06LA4	25	7000	-	13.5	108	1.25
9.5	151	1.1	143.2	"	"	7000	-	11.5	125	1.3
8.0	178	1.1	170.6	"	"	7000	-	9.5	150	1.35
6.6	210	0.95	204.7	"	"	7000	-	8.0	176	1.15
12.5	118	2.7	108.6	BK20-../D06LA4	33	8700	9000	15	98	3.2
11	132	2.5	124.2	BK20Z-../D06LA4	34	8700	9000	13.5	108	3.1
9.4	153	2.2	144.5	"	"	8700	9000	11.5	125	2.6
7.8	182	1.8	173.4	"	"	8700	9000	9.4	151	2.2
6.6	210	1.55	207.5	"	"	8700	9000	7.9	178	1.85
5.2	270	1.2	259.9	"	"	8700	9000	6.3	220	1.5
4.6	300	1.05	298.2	"	"	8700	9000	5.5	250	1.25
3.8	340	1.05	359.1	BK20G06-../D06LA4	38	8700	9000	4.6	280	1.3
3.2	405	0.89	429.7	"	"	8700	9000	3.8	340	1.05
2.9	445	0.81	480.4	"	"	8700	9000	3.4	380	0.95
9.4	153	2.9	145.1	BK30Z-../D06LA4	41	11200	12000	11.5	125	3.6
7.4	192	2.3	184.8	"	"	11200	12000	8.8	162	2.8
6.3	220	2.0	216.5	"	"	11200	12000	7.5	187	2.4
5.3	265	1.7	255.3	"	"	11200	12000	6.4	220	2.0
4.4	320	1.2	308.3	"	"	11200	12000	5.3	265	1.45
3.6	385	1.05	380.7	"	"	11200	12000	4.3	320	1.25
3.1	440	0.87	441.3	"	"	11200	12000	3.7	370	1.05
2.9	445	1.1	471.5	BK30G06-../D06LA4	44	11200	12000	3.5	370	1.3
2.4	540	0.91	567.0	"	"	11200	12000	2.9	445	1.1
2.1	610	0.8	652.5	"	"	11200	12000	2.5	510	0.96
5.5	250	3.1	246.6	BK40Z-../D06LA4	64	11700	17000	6.6	210	3.7
4.7	295	2.3	289.8	"	"	11700	17000	5.6	245	2.8
3.9	355	1.65	348.7	"	"	11700	17000	4.7	295	1.95
3.2	425	1.35	430.0	"	"	11700	17000	3.8	360	1.6
2.8	420	2.0	487.3	BK40G10-../D06LA4	68	11700	17000	3.4	335	2.5
2.5	470	1.8	540.0	"	"	11700	17000	3.0	385	2.2
2.1	560	1.5	660.2	"	"	11700	17000	2.5	465	1.85
1.8	660	1.3	756.7	"	"	11700	17000	2.2	530	1.6
1.4	870	0.98	998.3	"	"	11700	17000	1.7	710	1.2
1.2	1020	0.83	1189	"	"	11700	17000	1.4	870	0.98
4.2	330	3.1	328.2	BK50Z-../D06LA4	93	14100	26000	5.0	275	3.7
3.3	415	2.0	414.8	"	"	14100	26000	4.0	340	2.5
3.0	395	2.9	465.1	BK50G10-../D06LA4	97	14100	26000	3.5	330	3.5
2.4	500	2.3	568.6	"	"	14100	26000	2.9	405	2.8
2.1	570	2.0	651.7	"	"	14100	26000	2.5	475	2.4
1.6	760	1.5	859.8	"	"	14100	26000	1.9	640	1.8
1.4	880	1.3	1024	"	"	14100	26000	1.6	760	1.5
1.1	1120	1.05	1230	"	"	14100	26000	1.4	880	1.3
0.9	1150*	1.0	1549	"	"	14100	26000	1.1	1150*	1.0
1.4	920	2.7	1016	BK60G20-../D06LA4	123	16600	34000	1.6	770	3.2
1.1	1220	2.0	1322	"	"	16600	34000	1.3	980	2.6
0.85	1610	1.55	1618	"	"	16600	34000	1.1	1150	2.2



P = 0.18 кВт




50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
0.75	1830	1.35	1810	BK60G20-../D06LA4	123	16600	34000	0.9	1450	1.7
0.6	2350	1.05	2371	"	"	16600	34000	0.7	1950	1.3
0.5	2500*	1.0	2733	"	"	16600	34000	0.6	2500*	1.0
0.8	1720	3.3	1696	BK70G20-../D06LA4	201	24100	50000	1.0	1290	4.4
0.7	1940	2.9	2040	"	"	24100	50000	0.8	1630	3.5
0.55	2500	2.3	2578	"	"	24100	50000	0.65	2000	2.9
0.45	3150	1.8	3041	"	"	24100	50000	0.55	2450	2.3
0.39	3700	1.55	3505	"	"	24100	50000	0.47	2950	1.95
0.35	4200	1.35	3894	"	"	24100	50000	0.42	3350	1.7
0.3	5000	1.15	4531	"	"	24100	50000	0.36	4050	1.4
0.25	5700*	1.0	5436	"	"	24100	50000	0.3	5700*	1.0

P = 0.25 кВт

176	12.4	9.3	7.68	BK10-../D06LA4	23	2400	-	215	10.2	11
144	15.2	7.6	9.40	"	"	2700	-	173	12.6	9.1
114	19.2	6.0	11.93	"	"	3100	-	136	16.1	7.1
80	26.5	5.1	16.92	"	"	3700	-	96	22	6.2
73	29	6.9	18.52	"	"	4300	-	88	24	8.3
60	35.5	5.6	22.65	"	"	4650	-	72	29.5	6.8
47	45.5	4.4	28.76	"	"	5200	-	57	37.5	5.3
39.5	54	3.7	34.25	"	"	5600	-	47.5	45	4.4
33.5	64	3.1	40.79	"	"	6000	-	40	53	3.8
28	75	2.7	48.96	"	"	6400	-	33.5	63	3.2
22	96	2.1	61.68	"	"	7000	-	26.5	80	2.5
19	110	1.8	72.31	"	"	7000	-	22.5	93	2.2
15.5	134	1.35	89.30	"	"	7000	-	18.5	112	1.6
13.5	150	1.05	102.5	"	"	7000	-	16	126	1.25
8.0	245	0.82	170.6	BK10Z-../D06LA4	25	7000	-	9.5	205	0.98
18	116	2.8	76.79	BK20-../D06LA4	33	7500	9000	21.5	97	3.4
15.5	134	2.5	88.12	"	"	8000	9000	18.5	112	2.9
12.5	164	1.9	108.6	"	"	8700	9000	15	136	2.3
11	184	1.8	124.2	BK20Z-../D06LA4	34	8700	9000	13.5	150	2.2
9.4	210	1.55	144.5	"	"	8700	9000	11.5	174	1.9
7.8	250	1.3	173.4	"	"	8700	9000	9.4	210	1.55
6.6	295	1.1	207.5	"	"	8700	9000	7.9	245	1.35
5.2	375	0.88	259.9	"	"	8700	9000	6.3	310	1.05
13.5	150	3.0	102.4	BK30-../D06LA4	39	11200	12000	16	126	3.6
11	184	2.4	123.9	BK30Z-../D06LA4	41	11200	12000	13.5	150	3.0
9.4	210	2.1	145.1	"	"	11200	12000	11.5	174	2.6
7.4	265	1.7	184.8	"	"	11200	12000	8.8	225	2.0
6.3	310	1.45	216.5	"	"	11200	12000	7.5	260	1.75
5.3	365	1.25	255.3	"	"	11200	12000	6.4	305	1.5
4.4	440	0.88	308.3	"	"	11200	12000	5.3	365	1.05
8.0	245	3.2	169.0	BK40Z-../D06LA4	64	11700	17000	9.6	205	3.8
6.4	305	2.6	211.5	"	"	11700	17000	7.7	250	3.1
5.5	350	2.2	246.6	"	"	11700	17000	6.6	290	2.7
4.7	410	1.65	289.8	"	"	11700	17000	5.6	345	2.0
3.9	495	1.15	348.7	"	"	11700	17000	4.7	410	1.4
3.2	590	0.97	430.0	"	"	11700	17000	3.8	500	1.15
2.8	610	1.4	487.3	BK40G10-../D06LA4	68	11700	17000	3.4	495	1.7
2.5	680	1.25	540.0	"	"	11700	17000	3.0	560	1.5
2.1	810	1.05	660.2	"	"	11700	17000	2.5	680	1.25
1.8	950	0.89	756.7	"	"	11700	17000	2.2	770	1.1
1.7	1020	0.83	838.4	"	"	11700	17000	2.0	860	0.99




P = 0.25 кВт



50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
5.2	370	2.8	264.5	BK50Z-../D06LA4	93	14100	26000	6.2	310	3.4
4.2	460	2.2	328.2	"	"	14100	26000	5.0	385	2.6
3.3	570	1.5	414.8	"	"	14100	26000	4.0	475	1.8
3.0	570	2.0	465.1	BK50G10-../D06LA4	97	14100	26000	3.5	485	2.4
2.4	720	1.6	568.6	"	"	14100	26000	2.9	590	1.95
2.1	820	1.4	651.7	"	"	14100	26000	2.5	680	1.7
1.6	1090	1.05	859.8	"	"	14100	26000	1.9	910	1.25
1.4	1250	0.92	1024	"	"	14100	26000	1.6	1090	1.05
2.2	820	3.0	621.5	BK60G20-../D06LA4	123	16600	34000	2.7	620	4.0
1.8	1010	2.5	752.1	"	"	16600	34000	2.2	770	3.2
1.6	1150	2.2	887.8	"	"	16600	34000	1.9	920	2.7
1.4	1400	1.8	1016	"	"	16600	34000	1.6	1190	2.1
1.1	1830	1.35	1322	"	"	16600	34000	1.3	1500	1.65
0.85	2350	1.05	1618	"	"	16600	34000	1.1	1760	1.4
0.75	2500*	1.0	1810	"	"	16600	34000	0.9	2500*	1.0
0.7	2500*	1.0	2010	"	"	16600	34000	0.85	2500*	1.0
1.1	1790	3.2	1280	BK70G20-../D06LA4	201	24100	50000	1.3	1450	3.9
0.95	2050	2.8	1457	"	"	24100	50000	1.2	1560	3.7
0.8	2550	2.2	1696	"	"	24100	50000	1.0	1950	2.9
0.7	2850	2.0	2040	"	"	24100	50000	0.8	2450	2.3
0.55	3700	1.55	2578	"	"	24100	50000	0.65	3050	1.85
0.45	4650	1.25	3041	"	"	24100	50000	0.55	3650	1.55
0.39	5400	1.05	3505	"	"	24100	50000	0.47	4350	1.3
0.35	5700*	1.0	3894	"	"	24100	50000	0.42	5700*	1.0

P = 0.3 кВт

176	14.9	7.7	7.68	BK10-../D07LA4	26	2400	-	215	12.2	9.4
144	18.3	6.3	9.40	"	"	2700	-	173	15.2	7.6
114	23	5.0	11.93	"	"	3100	-	136	19.3	6.0
80	32	4.3	16.92	"	"	3700	-	96	26.5	5.1
73	35	5.7	18.52	"	"	4300	-	88	29	6.9
60	42.5	4.7	22.65	"	"	4650	-	72	35.5	5.6
47	54	3.7	28.76	"	"	5200	-	57	45	4.4
39.5	65	3.1	34.25	"	"	5600	-	47.5	54	3.7
33.5	76	2.6	40.79	"	"	6000	-	40	64	3.1
28	91	2.2	48.96	"	"	6400	-	33.5	76	2.6
22	115	1.75	61.68	"	"	7000	-	26.5	96	2.1
19	132	1.5	72.31	"	"	7000	-	22.5	112	1.8
15.5	160	1.1	89.30	"	"	7000	-	18.5	134	1.35
13.5	180	0.87	102.5	"	"	7000	-	16	152	1.05
22.5	113	2.9	61.30	BK20-../D07LA4	35	6500	9000	26.5	96	3.4
18	140	2.4	76.79	"	"	7500	9000	21.5	117	2.8
15.5	160	2.1	88.12	"	"	8000	9000	18.5	134	2.5
12.5	197	1.6	108.6	"	"	8700	9000	15	164	1.9
11	220	1.5	124.2	BK20Z-../D07LA4	37	8700	9000	13.5	180	1.85
9.4	255	1.3	144.5	"	"	8700	9000	11.5	205	1.6
7.8	300	1.1	173.4	"	"	8700	9000	9.4	250	1.3
6.6	355	0.93	207.5	"	"	8700	9000	7.9	295	1.1
15.5	158	2.8	88.38	BK30-../D07LA4	41	10600	12000	18.5	133	3.4
13.5	180	2.5	102.4	"	"	11200	12000	16	152	3.0
11	220	2.0	123.9	BK30Z-../D07LA4	44	11200	12000	13.5	180	2.5
9.4	255	1.75	145.1	"	"	11200	12000	11.5	205	2.2
7.4	320	1.4	184.8	"	"	11200	12000	8.8	270	1.65
6.3	370	1.2	216.5	"	"	11200	12000	7.5	310	1.45




P = 0.3 кВт

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
5.3	440	1.0	255.3	BK30Z-../D07LA4	44	11200	12000	6.4	365	1.25
9.5	250	3.1	143.0	BK40Z-../D07LA4	66	11700	17000	11.5	205	3.8
8.0	295	2.6	169.0	"	"	11700	17000	9.6	245	3.2
6.4	365	2.1	211.5	"	"	11700	17000	7.7	305	2.6
5.5	420	1.85	246.6	"	"	11700	17000	6.6	350	2.2
4.7	490	1.4	289.8	"	"	11700	17000	5.6	410	1.65
3.9	590	0.98	348.7	"	"	11700	17000	4.7	490	1.2
3.2	710	0.81	430.0	"	"	11700	17000	3.8	600	0.96
2.8	740	1.15	487.3	BK40G10-../D07LA4	71	11700	17000	3.4	600	1.4
2.5	830	1.0	540.0	"	"	11700	17000	3.0	680	1.25
2.1	990	0.86	660.2	"	"	11700	17000	2.5	830	1.0
6.6	355	3.0	206.8	BK50Z-../D07LA4	95	14100	26000	7.9	295	3.6
5.2	445	2.4	264.5	"	"	14100	26000	6.2	370	2.8
4.2	550	1.85	328.2	"	"	14100	26000	5.0	460	2.2
3.3	690	1.2	414.8	"	"	14100	26000	4.0	570	1.5
3.0	700	1.65	465.1	BK50G10-../D07LA4	99	14100	26000	3.5	590	1.95
2.4	870	1.3	568.6	"	"	14100	26000	2.9	720	1.6
2.1	1000	1.15	651.7	"	"	14100	26000	2.5	830	1.4
1.6	1320	0.87	859.8	"	"	14100	26000	1.9	1110	1.05
2.2	1040	2.4	621.5	BK60G20-../D07LA4	125	16600	34000	2.7	800	3.1
1.8	1270	1.95	752.1	"	"	16600	34000	2.2	980	2.6
1.6	1450	1.7	887.8	"	"	16600	34000	1.9	1170	2.1
1.4	1740	1.45	1016	"	"	16600	34000	1.6	1490	1.7
1.1	2250	1.1	1322	"	"	16600	34000	1.3	1860	1.35
0.85	2500*	1.0	1618	"	"	16600	34000	1.1	2500*	1.0
1.2	1950	2.9	1139	BK70G20-../D07LA4	204	24100	50000	1.5	1480	3.9
0.95	2550	2.2	1457	"	"	24100	50000	1.2	1950	2.9
0.8	3150	1.8	1696	"	"	24100	50000	1.0	2400	2.4
0.7	3550	1.6	2040	"	"	24100	50000	0.8	3050	1.85
0.55	4600	1.25	2578	"	"	24100	50000	0.65	3800	1.5
0.45	5700*	1.0	3041	"	"	24100	50000	0.55	5700*	1.0
0.39	5700*	1.0	3505	"	"	24100	50000	0.47	5700*	1.0

P = 0.37 кВт

176	18.4	6.3	7.68	BK10-../D07LA4	26	2400	-	215	15.1	7.6
144	22.5	5.1	9.40	"	"	2700	-	173	18.7	6.1
114	28.5	4.0	11.93	"	"	3100	-	136	23.5	4.9
80	39.5	3.4	16.92	"	"	3700	-	96	33	4.1
73	43.5	4.6	18.52	"	"	4300	-	88	36	5.6
60	53	3.8	22.65	"	"	4650	-	72	44	4.5
47	67	3.0	28.76	"	"	5200	-	57	55	3.6
39.5	80	2.5	34.25	"	"	5600	-	47.5	66	3.0
33.5	94	2.1	40.79	"	"	6000	-	40	79	2.5
28	112	1.8	48.96	"	"	6400	-	33.5	93	2.2
22	142	1.4	61.68	"	"	7000	-	26.5	118	1.7
19	163	1.25	72.31	"	"	7000	-	22.5	138	1.45
15.5	198	0.9	89.30	"	"	7000	-	18.5	166	1.05
32	99	3.3	42.70	BK20-../D07LA4	35	5800	9000	38	83	4.0
26.5	118	2.8	51.22	"	"	6300	9000	32	98	3.4
22.5	139	2.4	61.30	"	"	6500	9000	26.5	118	2.8
18	172	1.9	76.79	"	"	7500	9000	21.5	144	2.3
15.5	198	1.65	88.12	"	"	8000	9000	18.5	166	2.0
12.5	240	1.3	108.6	"	"	8700	9000	15	200	1.6
11	270	1.2	124.2	BK20Z-../D07LA4	37	8700	9000	13.5	220	1.5

P = 0.37 кВт




50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
9.4	315	1.05	144.5	BK20Z-../D07LA4	37	8700	9000	11.5	255	1.3
7.8	375	0.88	173.4	"	"	8700	9000	9.4	310	1.05
23	135	3.3	59.27	BK30-../D07LA4	41	8900	12000	27.5	113	4.0
19	161	2.8	71.56	"	"	9700	12000	23	133	3.4
15.5	196	2.3	88.38	"	"	10600	12000	18.5	164	2.7
13.5	220	2.0	102.4	"	"	11200	12000	16	187	2.4
11	270	1.65	123.9	BK30Z-../D07LA4	44	11200	12000	13.5	220	2.0
9.4	315	1.45	145.1	"	"	11200	12000	11.5	255	1.75
7.4	395	1.15	184.8	"	"	11200	12000	8.8	330	1.35
6.3	455	0.99	216.5	"	"	11200	12000	7.5	385	1.15
5.3	540	0.83	255.3	"	"	11200	12000	6.4	450	1.0
11.5	260	3.0	118.2	BK40Z-../D07LA4	66	11700	17000	14	210	3.7
9.5	310	2.5	143.0	"	"	11700	17000	11.5	255	3.1
8.0	365	2.1	169.0	"	"	11700	17000	9.6	305	2.6
6.4	450	1.75	211.5	"	"	11700	17000	7.7	375	2.1
5.5	520	1.5	246.6	"	"	11700	17000	6.6	430	1.8
4.7	600	1.15	289.8	"	"	11700	17000	5.6	510	1.35
3.9	730	0.8	348.7	"	"	11700	17000	4.7	600	0.97
2.8	930	0.91	487.3	BK40G10-../D07LA4	71	11700	17000	3.4	760	1.1
2.5	1040	0.82	540.0	"	"	11700	17000	3.0	860	0.99
8.9	325	3.2	153.3	BK50Z-../D07LA4	95	14100	26000	11	265	4.0
6.6	435	2.4	206.8	"	"	14100	26000	7.9	365	2.9
5.2	550	1.9	264.5	"	"	14100	26000	6.2	460	2.3
4.2	680	1.5	328.2	"	"	14100	26000	5.0	570	1.75
3.3	850	0.99	414.8	"	"	14100	26000	4.0	700	1.2
3.0	870	1.3	465.1	BK50G10-../D07LA4	99	14100	26000	3.5	740	1.55
2.4	1090	1.05	568.6	"	"	14100	26000	2.9	900	1.3
2.1	1250	0.92	651.7	"	"	14100	26000	2.5	1050	1.1
1.9	1380	0.83	722.2	"	"	14100	26000	2.3	1140	1.0
2.2	1340	1.85	621.5	BK60G20-../D07LA4	125	16600	34000	2.7	1040	2.4
1.8	1640	1.5	752.1	"	"	16600	34000	2.2	1290	1.95
1.6	1870	1.35	887.8	"	"	16600	34000	1.9	1520	1.65
1.4	2200	1.15	1016	"	"	16600	34000	1.6	1900	1.3
1.1	2850	0.88	1322	"	"	16600	34000	1.3	2350	1.05
1.6	1850	3.1	847.7	BK70G20-../D07LA4	204	24100	50000	2.0	1410	4.0
1.4	2100	2.7	964.6	"	"	24100	50000	1.7	1670	3.4
1.2	2500	2.3	1139	"	"	24100	50000	1.5	1920	3.0
0.95	3250	1.75	1457	"	"	24100	50000	1.2	2500	2.3
0.8	3950	1.45	1696	"	"	24100	50000	1.0	3100	1.85
0.7	4500	1.25	2040	"	"	24100	50000	0.8	3900	1.45
0.55	5700*	1.0	2578	"	"	24100	50000	0.65	5700*	1.0

P = 0.55 кВт

235	20.5	5.1	6.02	BK10-../D08MA4	27	2100	-	280	17.2	6.1
183	26	4.4	7.68	"	"	2400	-	220	21.5	5.3
149	32	3.6	9.40	"	"	2700	-	179	26.5	4.3
118	40.5	2.8	11.93	"	"	3100	-	141	34	3.4
97	48.5	4.1	14.50	"	"	3900	-	116	40.5	4.9
83	56	2.4	16.92	"	"	3700	-	100	47	2.9
76	62	3.2	18.52	"	"	4300	-	91	51	3.9
62	76	2.6	22.65	"	"	4650	-	75	63	3.2
49	96	2.1	28.76	"	"	5200	-	59	80	2.5
41	115	1.75	34.25	"	"	5600	-	49.5	95	2.1
34.5	137	1.45	40.79	"	"	6000	-	41.5	113	1.75


P = 0.55 кВт



Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
29	161	1.25	48.96	BK10-../D08MA4	27	6400	-	34.5	135	1.5
23	200	1.0	61.68	"	"	7000	-	27.5	169	1.2
19.5	235	0.85	72.31	"	"	7000	-	23.5	196	1.0
38.5	122	2.7	36.69	BK20-../D08MA4	36	5400	9000	46	102	3.2
33	143	2.3	42.70	"	"	5800	9000	39.5	119	2.8
27.5	169	1.95	51.22	"	"	6300	9000	33	141	2.3
23	200	1.65	61.30	"	"	6500	9000	27.5	169	1.95
18.5	245	1.35	76.79	"	"	7500	9000	22	210	1.55
16	285	1.15	88.12	"	"	8000	9000	19.5	230	1.45
13	345	0.91	108.6	"	"	8700	9000	15.5	290	1.1
11.5	385	0.86	124.2	BK20Z-../D08MA4	38	8700	9000	14	315	1.05
33	141	3.2	42.89	BK30-../D08MA4	42	7800	12000	39.5	118	3.8
28	165	2.7	50.27	"	"	8300	12000	33.5	137	3.3
24	192	2.3	59.27	"	"	8900	12000	28.5	162	2.8
20	225	2.0	71.56	"	"	9700	12000	23.5	194	2.3
16	280	1.6	88.38	"	"	10600	12000	19.5	230	1.95
14	315	1.45	102.4	"	"	11200	12000	16.5	270	1.65
11.5	385	1.15	123.9	BK30Z-../D08MA4	45	11200	12000	14	315	1.45
9.7	450	1.0	145.1	"	"	11200	12000	12	365	1.25
17	265	2.9	84.36	BK40-../D08MA4	63	10700	17000	20	225	3.5
13.5	330	2.4	104.0	"	"	11700	17000	16.5	270	2.9
12	370	2.1	118.2	BK40Z-../D08MA4	67	11700	17000	14.5	305	2.6
9.8	450	1.75	143.0	"	"	11700	17000	12	365	2.1
8.3	520	1.5	169.0	"	"	11700	17000	10	435	1.8
6.7	640	1.2	211.5	"	"	11700	17000	8.0	530	1.45
5.7	740	1.05	246.6	"	"	11700	17000	6.9	610	1.3
4.9	860	0.8	289.8	"	"	11700	17000	5.8	730	0.94
12.5	355	3.0	115.4	BK50Z-../D08MA4	96	14100	26000	15	295	3.6
9.2	470	2.2	153.3	"	"	14100	26000	11	395	2.7
6.8	630	1.65	206.8	"	"	14100	26000	8.2	520	2.0
5.3	800	1.3	264.5	"	"	14100	26000	6.4	660	1.6
4.3	980	1.05	328.2	"	"	14100	26000	5.2	810	1.25
3.1	1290	0.89	465.1	BK50G10-../D08MA4	100	14100	26000	3.7	1080	1.05
2.8	1420	0.81	513.4	"	"	14100	26000	3.3	1210	0.95
6.9	760	3.0	205.0	BK60Z-../D08MA4	119	16600	34000	8.2	640	3.6
5.9	890	2.6	239.7	"	"	16600	34000	7.1	730	3.2
5.3	990	2.3	268.2	"	"	16600	34000	6.3	830	2.8
4.5	1160	2.0	317.7	"	"	16600	34000	5.3	990	2.3
4.0	1310	1.75	355.5	"	"	16600	34000	4.8	1090	2.1
3.5	1500	1.55	411.5	"	"	16600	34000	4.1	1280	1.8
3.1	1690	1.35	460.4	"	"	16600	34000	3.7	1410	1.65
2.9	1810	1.25	498.0	"	"	16600	34000	3.4	1540	1.5
2.6	2000	1.15	557.2	"	"	16600	34000	3.1	1690	1.35
2.3	2000	1.25	621.5	BK60G20-../D08MA4	126	16600	34000	2.8	1610	1.55
1.9	2400	1.05	752.1	"	"	16600	34000	2.3	1960	1.3
1.6	2900	0.86	887.8	"	"	16600	34000	1.9	2400	1.05
3.3	1590	3.3	432.1	BK70Z-../D08MA4	207	24100	50000	3.9	1340	3.9
2.8	1870	2.8	501.8	"	"	24100	50000	3.4	1540	3.4
2.5	2100	2.5	570.8	"	"	24100	50000	3.0	1750	3.0
2.2	2350	2.2	644.9	"	"	24100	50000	2.7	1940	2.7
2.0	2600	2.0	733.6	"	"	24100	50000	2.3	2250	2.3
1.7	2700	2.1	847.7	BK70G20-../D08MA4	205	24100	50000	2.0	2250	2.5
1.5	3050	1.85	964.6	"	"	24100	50000	1.8	2500	2.3
1.3	3600	1.6	1139	"	"	24100	50000	1.5	3050	1.85
1.1	4350	1.3	1280	"	"	24100	50000	1.4	3350	1.7

P = 0.55 кВт




Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
0.85	5700*	1.0	1696	BK70G20-../D08MA4	205	24100	50000	1.0	5700*	1.0
0.7	5700*	1.0	2040	"	"	24100	50000	0.85	5700*	1.0
1.1	3750	3.1	1307	BK80G40-../D08MA4	347	30000	75000	1.3	3000	3.8
0.9	4600	2.5	1583	"	"	30000	75000	1.1	3550	3.2
0.8	5200	2.2	1775	"	"	30000	75000	0.95	4200	2.7
0.65	6600	1.75	2205	"	"	30000	75000	0.8	5100	2.3
0.5	9000	1.3	2811	"	"	30000	75000	0.6	7200	1.6
0.38	11500*	1.0	3776	"	"	30000	75000	0.45	11500*	1.0
0.55	7400	2.5	2764	BK90G50-../D08MA4	620	49400	120000	0.65	5900	3.1
0.46	9300	2.0	3065	"	"	49400	120000	0.55	7400	2.5
0.39	11300	1.65	3672	"	"	49400	120000	0.46	9300	2.0
0.35	12900	1.45	4070	"	"	49400	120000	0.42	10300	1.8
0.29	16000	1.15	4952	"	"	49400	120000	0.34	13300	1.4
0.26	18000	1.05	5491	"	"	49400	120000	0.31	14800	1.25
0.23	18500*	1.0	6335	"	"	49400	120000	0.27	18500*	1.0

P = 0.75 кВт

235	28	3.8	6.02	BK10-../D08LA4	29	2100	-	280	23.5	4.5
183	36	3.2	7.68	"	"	2400	-	220	29.5	3.9
149	44	2.6	9.40	"	"	2700	-	179	36.5	3.2
118	55	2.1	11.93	"	"	3100	-	141	46.5	2.5
97	66	3.0	14.50	"	"	3900	-	116	55	3.6
83	77	1.75	16.92	"	"	3700	-	100	64	2.1
76	84	2.4	18.52	"	"	4300	-	91	70	2.9
62	103	1.95	22.65	"	"	4650	-	75	85	2.4
49	131	1.55	28.76	"	"	5200	-	59	109	1.85
41	157	1.25	34.25	"	"	5600	-	49.5	130	1.55
34.5	186	1.1	40.79	"	"	6000	-	41.5	155	1.3
29	215	0.93	48.96	"	"	6400	-	34.5	184	1.1
81	80	2.9	17.42	BK20-../D08LA4	38	3250	9000	97	67	3.4
73	88	3.8	19.39	"	"	4050	9000	87	74	4.5
58	111	3.0	24.29	"	"	4500	9000	70	92	3.6
49	131	2.5	28.66	"	"	4850	9000	59	109	3.0
38.5	167	2.0	36.69	"	"	5400	9000	46	140	2.4
33	195	1.7	42.70	"	"	5800	9000	39.5	163	2.0
27.5	230	1.45	51.22	"	"	6300	9000	33	193	1.7
23	275	1.2	61.30	"	"	6500	9000	27.5	230	1.45
18.5	340	0.97	76.79	"	"	7500	9000	22	285	1.15
16	385	0.86	88.12	"	"	8000	9000	19.5	315	1.05
42	153	2.9	33.70	BK30-../D08LA4	44	7000	12000	50	128	3.5
33	193	2.3	42.89	"	"	7800	12000	39.5	161	2.8
28	225	2.0	50.27	"	"	8300	12000	33.5	188	2.4
24	260	1.75	59.27	"	"	8900	12000	28.5	220	2.0
20	310	1.45	71.56	"	"	9700	12000	23.5	265	1.7
16	380	1.2	88.38	"	"	10600	12000	19.5	315	1.45
14	430	1.05	102.4	"	"	11200	12000	16.5	365	1.25
11.5	520	0.87	123.9	BK30Z-../D08LA4	47	11200	12000	14	430	1.05
23.5	265	2.9	59.66	BK40-../D08LA4	64	9100	17000	28.5	220	3.5
20	310	2.5	70.11	"	"	9800	17000	24	255	3.1
17	365	2.1	84.36	"	"	10700	17000	20	310	2.5
13.5	450	1.75	104.0	"	"	11700	17000	16.5	365	2.1
12	500	1.55	118.2	BK40Z-../D08LA4	69	11700	17000	14.5	415	1.9
9.8	610	1.3	143.0	"	"	11700	17000	12	500	1.55
8.3	710	1.1	169.0	"	"	11700	17000	10	590	1.3

P = 0.75 кВт




50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
6.7	870	0.9	211.5	BK40Z-../D08LA4	69	11700	17000	8.0	730	1.05
19	325	3.2	75.40	BK50-../D08LA4	93	12600	26000	22.5	275	3.8
15	410	2.6	95.29	"	"	14100	26000	18	340	3.1
12.5	485	2.2	115.4	BK50Z-../D08LA4	98	14100	26000	15	405	2.6
9.2	640	1.65	153.3	"	"	14100	26000	11	540	1.95
6.8	860	1.2	206.8	"	"	14100	26000	8.2	710	1.5
5.3	1090	0.96	264.5	"	"	14100	26000	6.4	900	1.15
9.2	770	3.0	153.7	BK60Z-../D08LA4	120	16600	34000	11	650	3.5
7.7	930	2.5	183.2	"	"	16600	34000	9.2	770	3.0
6.9	1030	2.2	205.0	"	"	16600	34000	8.2	870	2.6
5.9	1210	1.9	239.7	"	"	16600	34000	7.1	1000	2.3
5.3	1350	1.7	268.2	"	"	16600	34000	6.3	1130	2.0
4.5	1590	1.45	317.7	"	"	16600	34000	5.3	1350	1.7
4.0	1790	1.3	355.5	"	"	16600	34000	4.8	1490	1.55
3.5	2000	1.15	411.5	"	"	16600	34000	4.1	1740	1.3
3.1	2300	1.0	460.4	"	"	16600	34000	3.7	1930	1.2
2.9	2450	0.94	498.0	"	"	16600	34000	3.4	2100	1.1
2.6	2750	0.84	557.2	"	"	16600	34000	3.1	2300	1.0
2.3	2850	0.88	621.5	BK60G20-../D08LA4	128	16600	34000	2.8	2250	1.1
4.2	1700	3.1	333.6	BK70Z-../D08LA4	209	24100	50000	5.1	1400	3.7
3.7	1930	2.7	379.9	"	"	24100	50000	4.5	1590	3.3
3.3	2150	2.4	432.1	"	"	24100	50000	3.9	1830	2.8
2.8	2550	2.0	501.8	"	"	24100	50000	3.4	2100	2.5
2.5	2850	1.8	570.8	"	"	24100	50000	3.0	2350	2.2
2.2	3250	1.6	644.9	"	"	24100	50000	2.7	2650	1.95
2.0	3550	1.45	733.6	"	"	24100	50000	2.3	3100	1.7
1.7	3850	1.5	847.7	BK70G20-../D08LA4	206	24100	50000	2.0	3200	1.8
1.5	4350	1.3	964.6	"	"	24100	50000	1.8	3550	1.6
1.3	5000	1.15	1139	"	"	24100	50000	1.5	4300	1.35
1.1	6100	0.93	1280	"	"	24100	50000	1.4	4700	1.2
1.0	6700	0.85	1457	"	"	24100	50000	1.2	5500	1.05
1.5	3850	3.0	963.0	BK80G40-../D08LA4	348	30000	75000	1.8	3050	3.8
1.3	4450	2.6	1079	"	"	30000	75000	1.6	3450	3.3
1.1	5400	2.1	1307	"	"	30000	75000	1.3	4450	2.6
0.9	6700	1.7	1583	"	"	30000	75000	1.1	5200	2.2
0.8	7600	1.5	1775	"	"	30000	75000	0.95	6200	1.85
0.65	9600	1.2	2205	"	"	30000	75000	0.8	7500	1.55
0.5	11500*	1.0	2811	"	"	30000	75000	0.6	11500*	1.0
0.45	11500*	1.0	3120	"	"	30000	75000	0.55	11500*	1.0
0.9	6400	2.9	1579	BK90G50-../D08LA4	621	49400	120000	1.1	5000	3.7
0.8	7200	2.6	1803	"	"	49400	120000	0.95	5800	3.2
0.7	8300	2.2	2016	"	"	49400	120000	0.85	6500	2.8
0.55	10900	1.7	2764	"	"	49400	120000	0.65	8900	2.1
0.46	13400	1.4	3065	"	"	49400	120000	0.55	10900	1.7
0.39	16200	1.15	3672	"	"	49400	120000	0.46	13400	1.4
0.35	18300	1.0	4070	"	"	49400	120000	0.42	14900	1.25
0.29	18500*	1.0	4952	"	"	49400	120000	0.34	18500*	1.0

P = 1.1 кВт

235	41	2.6	6.02	BK10-../D09SA4	32	2100	-	280	34.5	3.0
183	52	2.2	7.68	"	"	2400	-	220	43.5	2.6
149	64	1.8	9.40	"	"	2700	-	179	53	2.2
118	81	1.4	11.93	"	"	3100	-	141	68	1.7
97	97	2.1	14.50	"	"	3900	-	116	81	2.5


P = 1.1 кВт



Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
83	113	1.2	16.92	BK10-../D09SA4	32	3700	-	100	94	1.45
76	124	1.6	18.52	"	"	4300	-	91	103	1.95
62	152	1.3	22.65	"	"	4650	-	75	126	1.6
49	192	1.05	28.76	"	"	5200	-	59	160	1.25
41	230	0.87	34.25	"	"	5600	-	49.5	191	1.05
120	80	2.9	11.69	BK20-../D09SA4	42	2400	8800	144	67	3.4
95	99	3.3	14.75	"	"	3650	9000	114	82	4.0
81	118	1.95	17.42	"	"	3250	9000	97	98	2.4
73	129	2.6	19.39	"	"	4050	9000	87	108	3.1
58	163	2.0	24.29	"	"	4500	9000	70	135	2.4
49	192	1.7	28.66	"	"	4850	9000	59	160	2.1
38.5	245	1.35	36.69	"	"	5400	9000	46	205	1.6
33	285	1.15	42.70	"	"	5800	9000	39.5	235	1.4
27.5	335	0.99	51.22	"	"	6300	9000	33	280	1.2
23	405	0.81	61.30	"	"	6500	9000	27.5	335	0.99
68	140	2.3	20.85	BK30-../D09SA4	48	5000	12000	81	118	2.7
61	154	2.9	23.20	"	"	5900	12000	73	129	3.5
49	192	2.3	28.76	"	"	6500	12000	59	160	2.8
42	225	2.0	33.70	"	"	7000	12000	50	189	2.4
33	280	1.6	42.89	"	"	7800	12000	39.5	235	1.9
28	330	1.35	50.27	"	"	8300	12000	33.5	275	1.65
24	385	1.15	59.27	"	"	8900	12000	28.5	320	1.4
20	455	0.99	71.56	"	"	9700	12000	23.5	385	1.15
16	560	0.8	88.38	"	"	10600	12000	19.5	460	0.98
34.5	270	2.9	40.88	BK40-../D09SA4	68	7600	17000	41.5	225	3.5
27.5	335	2.3	51.18	"	"	8400	17000	33	280	2.8
23.5	390	2.0	59.66	"	"	9100	17000	28.5	320	2.4
20	455	1.7	70.11	"	"	9800	17000	24	380	2.1
17	530	1.45	84.36	"	"	10700	17000	20	455	1.7
13.5	660	1.2	104.0	"	"	11700	17000	16.5	540	1.45
12	740	1.05	118.2	BK40Z-../D09SA4	73	11700	17000	14.5	610	1.3
9.8	900	0.87	143.0	"	"	11700	17000	12	730	1.05
29.5	315	3.3	47.50	BK50-../D09SA4	97	10100	25700	35.5	260	4.0
23.5	390	2.7	60.76	"	"	11400	26000	28	330	3.2
19	480	2.2	75.40	"	"	12600	26000	22.5	405	2.6
15	600	1.75	95.29	"	"	14100	26000	18	500	2.1
12.5	710	1.5	115.4	BK50Z-../D09SA4	101	14100	26000	15	590	1.8
9.2	940	1.1	153.3	"	"	14100	26000	11	790	1.35
6.8	1260	0.83	206.8	"	"	14100	26000	8.2	1050	1.0
14	750	3.1	101.2	BK60-../D09SA4	105	13900	34000	17	610	3.8
12.5	840	2.7	113.2	"	"	15000	34000	15	700	3.3
11.5	910	2.5	122.5	"	"	15500	34000	14	750	3.1
10.5	1000	2.3	137.0	"	"	16600	34000	12.5	840	2.7
9.2	1140	2.0	153.7	BK60Z-../D09SA4	124	16600	34000	11	950	2.4
7.7	1360	1.7	183.2	"	"	16600	34000	9.2	1140	2.0
6.9	1520	1.5	205.0	"	"	16600	34000	8.2	1280	1.8
5.9	1780	1.3	239.7	"	"	16600	34000	7.1	1470	1.55
5.3	1980	1.15	268.2	"	"	16600	34000	6.3	1660	1.4
4.5	2300	1.0	317.7	"	"	16600	34000	5.3	1980	1.15
4.0	2600	0.88	355.5	"	"	16600	34000	4.8	2150	1.05
6.2	1690	3.1	226.2	BK70Z-../D09SA4	212	24100	50000	7.5	1400	3.7
5.5	1910	2.7	257.3	"	"	24100	50000	6.6	1590	3.3
4.8	2150	2.4	293.3	"	"	24100	50000	5.8	1810	2.9
4.2	2500	2.1	333.6	"	"	24100	50000	5.1	2050	2.5
3.7	2800	1.85	379.9	"	"	24100	50000	4.5	2300	2.3

P = 1.1 кВт




Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/мин	M ₂ , Нм	f _B						n ₂ , 1/мин	M ₂ , Нм	f _B
3.3	3150	1.65	432.1	BK70Z-../D09SA4	212	24100	50000	3.9	2650	1.95
2.8	3750	1.4	501.8	"	"	24100	50000	3.4	3050	1.7
2.5	4200	1.25	570.8	"	"	24100	50000	3.0	3500	1.5
2.2	4750	1.1	644.9	"	"	24100	50000	2.7	3850	1.35
2.0	5200	1.0	733.6	"	"	24100	50000	2.3	4550	1.15
1.7	5800	0.98	847.7	BK70G20-../D09SA4	210	24100	50000	2.0	4850	1.2
1.5	6500	0.88	964.6	"	"	24100	50000	1.8	5400	1.05
2.9	3600	3.2	499.5	BK80Z-../D09SA4	341	30000	75000	3.4	3050	3.8
2.6	4000	2.9	559.5	"	"	30000	75000	3.1	3350	3.4
2.4	3600	3.2	607.8	BK80G40-../D09SA4	352	30000	75000	2.8	3000	3.8
2.1	4150	2.8	680.9	"	"	30000	75000	2.5	3350	3.4
1.7	5200	2.2	847.2	"	"	30000	75000	2.0	4300	2.7
1.5	6100	1.9	963.0	"	"	30000	75000	1.8	4900	2.3
1.3	7000	1.65	1079	"	"	30000	75000	1.6	5500	2.1
1.1	8500	1.35	1307	"	"	30000	75000	1.3	7000	1.65
0.9	10400	1.1	1583	"	"	30000	75000	1.1	8300	1.4
0.8	11500*	1.0	1775	"	"	30000	75000	0.95	11500*	1.0
1.4	6100	3.0	1008	BK90G50-../D09SA4	625	49400	120000	1.7	4800	3.9
1.1	8300	2.2	1363	"	"	49400	120000	1.3	6800	2.7
0.9	10100	1.85	1579	"	"	49400	120000	1.1	8000	2.3
0.8	11400	1.6	1803	"	"	49400	120000	0.95	9300	2.0
0.7	13000	1.4	2016	"	"	49400	120000	0.85	10400	1.8
0.55	16900	1.1	2764	"	"	49400	120000	0.65	14000	1.3
0.46	18500*	1.0	3065	"	"	49400	120000	0.55	18500*	1.0

P = 1.5 кВт

235	56	1.9	6.02	BK10-../D09LA4	36	2100	-	280	47	2.2
183	72	1.6	7.68	"	"	2400	-	220	59	1.95
149	88	1.3	9.40	"	"	2700	-	179	73	1.6
118	111	1.05	11.93	"	"	3100	-	141	93	1.25
97	132	1.5	14.50	"	"	3900	-	116	111	1.8
83	155	0.88	16.92	"	"	3700	-	100	128	1.05
76	169	1.2	18.52	"	"	4300	-	91	141	1.4
62	205	0.98	22.65	"	"	4650	-	75	171	1.15
177	74	3.1	7.91	BK20-../D09LA4	46	1330	7600	215	61	3.8
142	92	2.5	9.91	"	"	1910	8300	170	77	3.0
120	109	2.1	11.69	"	"	2400	8800	144	91	2.5
95	135	2.4	14.75	"	"	3650	9000	114	113	2.9
81	160	1.45	17.42	"	"	3250	9000	97	134	1.7
73	176	1.9	19.39	"	"	4050	9000	87	148	2.2
58	220	1.5	24.29	"	"	4500	9000	70	184	1.8
49	260	1.25	28.66	"	"	4850	9000	59	215	1.55
38.5	330	1.0	36.69	"	"	5400	9000	46	280	1.2
33	390	0.85	42.70	"	"	5800	9000	39.5	325	1.0
118	111	2.9	11.93	BK30-../D09LA4	52	3650	12000	141	93	3.4
101	129	2.5	13.98	"	"	4050	12000	121	107	3.0
97	132	3.4	14.50	"	"	4900	12000	116	111	4.1
78	165	2.7	17.95	"	"	5300	12000	94	137	3.3
68	191	1.7	20.85	"	"	5000	12000	81	160	2.0
61	210	2.1	23.20	"	"	5900	12000	73	176	2.6
49	260	1.75	28.76	"	"	6500	12000	59	215	2.1
42	305	1.5	33.70	"	"	7000	12000	50	255	1.75
33	385	1.15	42.89	"	"	7800	12000	39.5	320	1.4
28	450	1.0	50.27	"	"	8300	12000	33.5	375	1.2


P = 1.5 кВт



Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/мин	M ₂ , Нм	f _B						n ₂ , 1/мин	M ₂ , Нм	f _B
24	520	0.87	59.27	BK30-../D09LA4	52	8900	12000	28.5	440	1.0
49	260	3.0	28.59	BK40-../D09LA4	72	6300	17000	59	215	3.6
40.5	315	2.5	34.61	"	"	6900	17000	49	260	3.0
34.5	370	2.1	40.88	"	"	7600	17000	41.5	310	2.5
27.5	455	1.7	51.18	"	"	8400	17000	33	380	2.1
23.5	530	1.45	59.66	"	"	9100	17000	28.5	440	1.75
20	620	1.25	70.11	"	"	9800	17000	24	510	1.55
17	730	1.05	84.36	"	"	10700	17000	20	620	1.25
13.5	900	0.87	104.0	"	"	11700	17000	16.5	730	1.05
40	320	3.3	35.21	BK50-../D09LA4	101	8700	23100	48	265	4.0
29.5	430	2.4	47.50	"	"	10100	25700	35.5	355	3.0
23.5	530	2.0	60.76	"	"	11400	26000	28	450	2.3
19	650	1.6	75.40	"	"	12600	26000	22.5	550	1.9
15	820	1.3	95.29	"	"	14100	26000	18	680	1.55
12.5	970	1.1	115.4	BK50Z-../D09LA4	105	14100	26000	15	810	1.3
9.2	1290	0.81	153.3	"	"	14100	26000	11	1080	0.97
18	790	2.9	78.13	BK60-../D09LA4	109	11900	34000	22	650	3.5
16.5	860	2.7	87.41	"	"	12900	34000	19.5	730	3.2
14	1020	2.3	101.2	"	"	13900	34000	17	840	2.7
12.5	1140	2.0	113.2	"	"	15000	34000	15	950	2.4
11.5	1240	1.85	122.5	"	"	15500	34000	14	1020	2.3
10.5	1360	1.7	137.0	"	"	16600	34000	12.5	1140	2.0
9.2	1550	1.5	153.7	BK60Z-../D09LA4	128	16600	34000	11	1300	1.75
7.7	1860	1.25	183.2	"	"	16600	34000	9.2	1550	1.5
6.9	2050	1.1	205.0	"	"	16600	34000	8.2	1740	1.3
5.9	2400	0.96	239.7	"	"	16600	34000	7.1	2000	1.15
5.3	2700	0.85	268.2	"	"	16600	34000	6.3	2250	1.0
9.1	1570	3.3	154.4	BK70-../D09LA4	195	21900	50000	11	1300	4.0
8.0	1790	2.9	175.7	"	"	24100	50000	9.6	1490	3.5
7.4	1930	2.7	190.4	BK70Z-../D09LA4	216	24100	50000	8.9	1600	3.3
6.2	2300	2.3	226.2	"	"	24100	50000	7.5	1910	2.7
5.5	2600	2.0	257.3	"	"	24100	50000	6.6	2150	2.4
4.8	2950	1.75	293.3	"	"	24100	50000	5.8	2450	2.1
4.2	3400	1.55	333.6	"	"	24100	50000	5.1	2800	1.85
3.7	3850	1.35	379.9	"	"	24100	50000	4.5	3150	1.65
3.3	4300	1.2	432.1	"	"	24100	50000	3.9	3650	1.4
2.8	5100	1.0	501.8	"	"	24100	50000	3.4	4200	1.25
2.5	5700	0.91	570.8	"	"	24100	50000	3.0	4750	1.1
2.2	6500	0.8	644.9	"	"	24100	50000	2.7	5300	0.98
3.6	3950	2.9	389.0	BK80Z-../D09LA4	345	30000	75000	4.4	3250	3.5
3.3	4300	2.7	435.7	"	"	30000	75000	3.9	3650	3.2
2.9	4900	2.3	499.5	"	"	30000	75000	3.4	4200	2.7
2.6	5500	2.1	559.5	"	"	30000	75000	3.1	4600	2.5
2.4	5200	2.2	607.8	BK80G40-../D09LA4	356	30000	75000	2.8	4350	2.6
2.1	5900	1.95	680.9	"	"	30000	75000	2.5	4850	2.4
1.7	7500	1.55	847.2	"	"	30000	75000	2.0	6200	1.85
1.5	8600	1.35	963.0	"	"	30000	75000	1.8	7000	1.65
1.3	10000	1.15	1079	"	"	30000	75000	1.6	7900	1.45
1.1	12000	0.96	1307	"	"	30000	75000	1.3	10000	1.15
1.0	13100	0.88	1425	"	"	30000	75000	1.2	10700	1.05
2.2	6500	2.8	637.7	BK90Z-../D09LA4	618	49400	120000	2.7	5300	3.5
2.0	7100	2.6	713.5	"	"	49400	120000	2.4	5900	3.1
1.8	6600	2.8	821.0	BK90G50-../D09LA4	629	49400	120000	2.1	5400	3.4
1.6	7700	2.4	882.3	"	"	49400	120000	2.0	5900	3.1
1.4	8800	2.1	1008	"	"	49400	120000	1.7	7000	2.6

P = 1.5 кВт




50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
1.1	11800	1.55	1363	BK90G50-.../D09LA4	629	49400	120000	1.3	9800	1.9
0.9	14400	1.3	1579	"	"	49400	120000	1.1	11500	1.6
0.8	16100	1.15	1803	"	"	49400	120000	0.95	13300	1.4
0.7	18500*	1.0	2016	"	"	49400	120000	0.85	18500*	1.0

P = 2.2 кВт

235	82	1.3	6.02	BK10-.../D09XA4	40	2100	-	280	69	1.5
183	105	1.1	7.68	"	"	2400	-	220	87	1.3
149	129	0.89	9.40	"	"	2700	-	179	107	1.05
97	194	1.05	14.50	"	"	3900	-	116	163	1.25
76	245	0.82	18.52	"	"	4300	-	91	205	0.98
235	82	2.7	6.02	BK20-.../D09XA4	50	580	6800	280	69	3.2
177	109	2.1	7.91	"	"	1330	7600	215	89	2.6
142	136	1.7	9.91	"	"	1910	8300	170	113	2.0
120	161	1.45	11.69	"	"	2400	8800	144	134	1.7
95	199	1.65	14.75	"	"	3650	9000	114	165	2.0
81	235	0.98	17.42	"	"	3250	9000	97	197	1.15
73	255	1.3	19.39	"	"	4050	9000	87	215	1.55
58	325	1.0	24.29	"	"	4500	9000	70	270	1.2
49	385	0.86	28.66	"	"	4850	9000	59	320	1.05
235	82	2.6	6.02	BK30-.../D09XA4	56	1690	9600	280	69	3.1
188	102	2.6	7.45	"	"	2200	10400	230	84	3.2
146	132	2.4	9.63	"	"	3150	11500	175	110	2.9
118	163	1.95	11.93	"	"	3650	12000	141	137	2.3
101	189	1.7	13.98	"	"	4050	12000	121	158	2.0
97	194	2.3	14.50	"	"	4900	12000	116	163	2.8
78	240	1.9	17.95	"	"	5300	12000	94	200	2.3
68	280	1.15	20.85	"	"	5000	12000	81	235	1.35
61	305	1.5	23.20	"	"	5900	12000	73	255	1.75
49	385	1.15	28.76	"	"	6500	12000	59	320	1.4
42	450	1.0	33.70	"	"	7000	12000	50	375	1.2
33	560	0.8	42.89	"	"	7800	12000	39.5	470	0.96
119	162	3.0	11.86	BK40-.../D09XA4	76	1770	12200	142	136	3.6
97	194	4.0	14.50	"	"	4500	14300	116	163	4.8
78	240	3.3	18.05	"	"	4900	15300	94	200	3.9
63	300	2.6	22.44	"	"	5500	16500	75	250	3.1
49	385	2.0	28.59	"	"	6300	17000	59	320	2.4
40.5	465	1.7	34.61	"	"	6900	17000	49	385	2.0
34.5	540	1.45	40.88	"	"	7600	17000	41.5	455	1.7
27.5	670	1.15	51.18	"	"	8400	17000	33	560	1.4
23.5	780	1.0	59.66	"	"	9100	17000	28.5	640	1.2
20	910	0.86	70.11	"	"	9800	17000	24	760	1.05
79	240	3.0	17.92	BK50-.../D09XA4	105	4600	16800	94	200	3.6
73	255	4.1	19.33	"	"	6900	19200	87	215	4.9
53	355	3.0	26.51	"	"	7800	21200	64	295	3.6
40	470	2.2	35.21	"	"	8700	23100	48	390	2.7
29.5	630	1.65	47.50	"	"	10100	25700	35.5	520	2.0
23.5	780	1.35	60.76	"	"	11400	26000	28	660	1.6
19	960	1.1	75.40	"	"	12600	26000	22.5	810	1.3
15	1200	0.88	95.29	"	"	14100	26000	18	1000	1.05
28	750	3.1	50.40	BK60-.../D09XA4	113	9100	29800	33.5	620	3.7
24	870	2.6	58.95	"	"	9900	31500	28.5	730	3.2
21.5	970	2.4	65.95	"	"	10900	33000	25.5	820	2.8
18	1160	2.0	78.13	"	"	11900	34000	22	950	2.4

P = 2.2 кВт




50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
16.5	1270	1.8	87.41	BK60-../D09XA4	113	12900	34000	19.5	1070	2.1
14	1500	1.55	101.2	"	"	13900	34000	17	1230	1.85
12.5	1680	1.35	113.2	"	"	15000	34000	15	1400	1.65
11.5	1820	1.25	122.5	"	"	15500	34000	14	1500	1.55
10.5	2000	1.15	137.0	"	"	16600	34000	12.5	1680	1.35
9.2	2250	1.0	153.7	BK60Z-../D09XA4	132	16600	34000	11	1910	1.2
7.7	2700	0.85	183.2	"	"	16600	34000	9.2	2250	1.0
12	1750	3.0	120.2	BK70-../D09XA4	199	18600	50000	14	1500	3.5
10.5	2000	2.6	136.7	"	"	20700	50000	12.5	1680	3.1
9.1	2300	2.3	154.4	"	"	21900	50000	11	1910	2.7
8.0	2600	2.0	175.7	"	"	24100	50000	9.6	2150	2.4
7.4	2800	1.85	190.4	BK70Z-../D09XA4	220	24100	50000	8.9	2350	2.2
6.2	3350	1.55	226.2	"	"	24100	50000	7.5	2800	1.85
5.5	3800	1.35	257.3	"	"	24100	50000	6.6	3150	1.65
4.8	4350	1.2	293.3	"	"	24100	50000	5.8	3600	1.45
4.2	5000	1.05	333.6	"	"	24100	50000	5.1	4100	1.25
3.7	5600	0.93	379.9	"	"	24100	50000	4.5	4650	1.1
3.3	6300	0.83	432.1	"	"	24100	50000	3.9	5300	0.98
5.6	3750	3.1	253.3	BK80Z-../D09XA4	349	30000	75000	6.7	3100	3.7
4.7	4450	2.6	300.6	"	"	30000	75000	5.6	3750	3.1
4.2	5000	2.3	336.7	"	"	30000	75000	5.0	4200	2.7
3.6	5800	2.0	389.0	"	"	30000	75000	4.4	4750	2.4
3.3	6300	1.85	435.7	"	"	30000	75000	3.9	5300	2.2
2.9	7200	1.6	499.5	"	"	30000	75000	3.4	6100	1.9
2.6	8000	1.45	559.5	"	"	30000	75000	3.1	6700	1.7
2.4	8000	1.45	607.8	BK80G40-../D09XA4	360	30000	75000	2.8	6700	1.7
2.1	9100	1.25	680.9	"	"	30000	75000	2.5	7500	1.55
1.7	11400	1.0	847.2	"	"	30000	75000	2.0	9500	1.2
1.5	13100	0.88	963.0	"	"	30000	75000	1.8	10700	1.05
3.6	5800	3.2	389.1	BK90Z-../D09XA4	622	49400	120000	4.4	4750	3.9
3.3	6300	2.9	435.3	"	"	49400	120000	3.9	5300	3.5
2.9	7200	2.6	499.2	"	"	49400	120000	3.4	6100	3.0
2.6	8000	2.3	558.5	"	"	49400	120000	3.1	6700	2.8
2.2	9500	1.95	637.7	"	"	49400	120000	2.7	7700	2.4
2.0	10500	1.75	713.5	"	"	49400	120000	2.4	8700	2.1
1.8	10300	1.8	821.0	BK90G50-../D09XA4	633	49400	120000	2.1	8600	2.2
1.6	11900	1.55	882.3	"	"	49400	120000	2.0	9300	2.0
1.4	13600	1.35	1008	"	"	49400	120000	1.7	11000	1.7
1.1	17800	1.05	1363	"	"	49400	120000	1.3	14900	1.25
0.9	18500*	1.0	1579	"	"	49400	120000	1.1	18500*	1.0

P = 3.0 кВт

240	109	4.3	6.02	BK40-../D11SA4	84	470	9800	285	92	5.2
190	138	3.6	7.49	"	"	750	10500	230	114	4.3
153	172	2.9	9.31	"	"	1040	11200	184	143	3.4
120	215	2.3	11.86	"	"	1770	12200	145	181	2.7
98	260	3.0	14.50	"	"	4500	14300	118	215	3.6
79	325	2.4	18.05	"	"	4900	15300	95	270	2.9
64	400	1.95	22.44	"	"	5500	16500	77	330	2.4
50	510	1.55	28.59	"	"	6300	17000	60	425	1.85
41.5	620	1.25	34.61	"	"	6900	17000	49.5	520	1.5
35	730	1.05	40.88	"	"	7600	17000	42	610	1.3
80	325	2.2	17.92	BK50-../D11SA4	114	4600	16800	96	270	2.7
74	345	3.0	19.33	"	"	6900	19200	89	285	3.7
54	475	2.2	26.51	"	"	7800	21200	65	395	2.7

P = 3.0 кВт




Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
40.5	630	1.65	35.21	BK50-../D11SA4	114	8700	23100	49	520	2.0
30	840	1.25	47.50	"	"	10100	25700	36	700	1.5
23.5	1070	0.98	60.76	"	"	11400	26000	28.5	880	1.2
19	1310	0.8	75.40	"	"	12600	26000	23	1080	0.97
38	750	3.1	37.80	BK60-../D11SA4	124	7300	26500	45.5	620	3.7
32	890	2.6	45.05	"	"	8200	28300	38	750	3.1
28.5	1000	2.3	50.40	"	"	9100	29800	34	840	2.7
24.5	1160	2.0	58.95	"	"	9900	31500	29.5	970	2.4
22	1300	1.75	65.95	"	"	10900	33000	26	1100	2.1
18.5	1540	1.5	78.13	"	"	11900	34000	22	1300	1.75
16.5	1730	1.35	87.41	"	"	12900	34000	20	1430	1.6
14.5	1970	1.15	101.2	"	"	13900	34000	17	1680	1.35
13	2200	1.05	113.2	"	"	15000	34000	15.5	1840	1.25
12	2350	0.98	122.5	"	"	15500	34000	14	2000	1.15
10.5	2700	0.85	137.0	"	"	16600	34000	12.5	2250	1.0
18	1590	3.3	79.89	BK70-../D11SA4	203	14300	47600	21.5	1330	3.9
16	1790	2.9	90.96	"	"	15300	49900	19	1500	3.5
14	2000	2.6	103.5	"	"	17200	50000	17	1680	3.1
12	2350	2.2	120.2	"	"	18600	50000	14.5	1970	2.6
10.5	2700	1.95	136.7	"	"	20700	50000	13	2200	2.4
9.2	3100	1.7	154.4	"	"	21900	50000	11.5	2450	2.1
8.1	3500	1.5	175.7	"	"	24100	50000	9.8	2900	1.8
7.5	3800	1.35	190.4	BK70Z-../D11SA4	230	24100	50000	9.0	3150	1.65
6.3	4500	1.15	226.2	"	"	24100	50000	7.6	3750	1.4
5.6	5100	1.0	257.3	"	"	24100	50000	6.7	4250	1.2
4.9	5800	0.9	293.3	"	"	24100	50000	5.9	4850	1.05
8.3	3450	3.0	171.5	BK80-../D11SA4	318	30000	75000	10	2850	3.7
8.0	3550	3.2	177.6	BK80Z-../D11SA4	360	30000	75000	9.7	2950	3.9
7.2	3950	2.9	198.9	"	"	30000	75000	8.6	3300	3.5
6.3	4500	2.6	226.1	"	"	30000	75000	7.6	3750	3.1
5.7	5000	2.3	253.3	"	"	30000	75000	6.8	4200	2.7
4.8	5900	1.95	300.6	"	"	30000	75000	5.7	5000	2.3
4.3	6600	1.75	336.7	"	"	30000	75000	5.1	5600	2.1
3.7	7700	1.5	389.0	"	"	30000	75000	4.4	6500	1.75
3.3	8600	1.35	435.7	"	"	30000	75000	4.0	7100	1.6
2.9	9800	1.15	499.5	"	"	30000	75000	3.5	8100	1.4
2.6	11000	1.05	559.5	"	"	30000	75000	3.1	9200	1.25
2.4	11100	1.05	607.8	BK80G40-../D11SA4	368	30000	75000	2.9	9100	1.25
2.1	12800	0.9	680.9	"	"	30000	75000	2.6	10100	1.15
1.9	14200	0.81	756.3	"	"	30000	75000	2.3	11600	0.99
4.9	5800	3.2	295.6	BK90Z-../D11SA4	626	49400	120000	5.8	4900	3.8
4.3	6600	2.8	330.7	"	"	49400	120000	5.2	5500	3.4
3.7	7700	2.4	389.1	"	"	49400	120000	4.4	6500	2.8
3.3	8600	2.2	435.3	"	"	49400	120000	4.0	7100	2.6
2.9	9800	1.9	499.2	"	"	49400	120000	3.5	8100	2.3
2.6	11000	1.7	558.5	"	"	49400	120000	3.1	9200	2.0
2.3	12400	1.5	637.7	"	"	49400	120000	2.7	10600	1.75
2.0	14300	1.3	713.5	"	"	49400	120000	2.4	11900	1.55
1.8	14500	1.3	821.0	BK90G50-../D11SA4	642	49400	120000	2.1	12300	1.5
1.5	17700	1.05	1008	"	"	49400	120000	1.7	15500	1.2
1.3	20500	0.9	1127	"	"	49400	120000	1.6	16300	1.15

P = 4.0 кВт

240	146	3.2	6.02	BK40-../D11MA4	90	470	9800	285	123	3.9
190	184	2.7	7.49	"	"	750	10500	230	152	3.2


P = 4.0 кВт



Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
153	225	2.2	9.31	BK40-../D11MA4	90	1040	11200	184	191	2.6
120	290	1.7	11.86	"	"	1770	12200	145	240	2.1
98	350	2.2	14.50	"	"	4500	14300	118	290	2.7
79	435	1.8	18.05	"	"	4900	15300	95	360	2.2
64	530	1.45	22.44	"	"	5500	16500	77	445	1.75
50	680	1.15	28.59	"	"	6300	17000	60	570	1.35
41.5	820	0.95	34.61	"	"	6900	17000	49.5	690	1.15
35	980	0.8	40.88	"	"	7600	17000	42	810	0.96
142	245	3.3	10.00	BK50-../D11MA4	120	1220	13200	171	205	4.0
102	335	3.1	13.95	"	"	6100	17400	123	275	3.8
80	430	1.7	17.92	"	"	4600	16800	96	360	2.0
74	460	2.3	19.33	"	"	6900	19200	89	385	2.7
54	630	1.65	26.51	"	"	7800	21200	65	520	2.0
40.5	840	1.25	35.21	"	"	8700	23100	49	700	1.5
30	1130	0.93	47.50	"	"	10100	25700	36	940	1.1
52	730	3.2	27.36	BK60-../D11MA4	130	5600	23200	63	600	3.8
42.5	890	2.6	33.78	"	"	6500	25200	51	740	3.1
38	1000	2.3	37.80	"	"	7300	26500	45.5	830	2.8
32	1190	1.95	45.05	"	"	8200	28300	38	1000	2.3
28.5	1340	1.7	50.40	"	"	9100	29800	34	1120	2.1
24.5	1550	1.5	58.95	"	"	9900	31500	29.5	1290	1.8
22	1730	1.35	65.95	"	"	10900	33000	26	1460	1.6
18.5	2050	1.1	78.13	"	"	11900	34000	22	1730	1.35
16.5	2300	1.0	87.41	"	"	12900	34000	20	1910	1.2
14.5	2600	0.88	101.2	"	"	13900	34000	17	2200	1.05
23.5	1620	3.2	61.60	BK70-../D11MA4	209	11500	42800	28	1360	3.8
20.5	1860	2.8	70.23	"	"	12500	44800	24.5	1550	3.4
18	2100	2.5	79.89	"	"	14300	47600	21.5	1770	2.9
16	2350	2.2	90.96	"	"	15300	49900	19	2000	2.6
14	2700	1.95	103.5	"	"	17200	50000	17	2200	2.4
12	3150	1.65	120.2	"	"	18600	50000	14.5	2600	2.0
10.5	3600	1.45	136.7	"	"	20700	50000	13	2900	1.8
9.2	4150	1.25	154.4	"	"	21900	50000	11.5	3300	1.6
8.1	4700	1.1	175.7	"	"	24100	50000	9.8	3850	1.35
7.5	5000	1.05	190.4	BK70Z-../D11MA4	236	24100	50000	9.0	4200	1.25
6.3	6000	0.87	226.2	"	"	24100	50000	7.6	5000	1.05
11	3450	3.0	131.6	BK80-../D11MA4	324	24900	75000	13	2900	3.6
9.3	4100	2.6	153.1	"	"	27200	75000	11.5	3300	3.2
8.3	4600	2.3	171.5	"	"	30000	75000	10	3800	2.8
8.0	4750	2.4	177.6	BK80Z-../D11MA4	366	30000	75000	9.7	3900	2.9
7.2	5300	2.2	198.9	"	"	30000	75000	8.6	4400	2.6
6.3	6000	1.9	226.1	"	"	30000	75000	7.6	5000	2.3
5.7	6700	1.7	253.3	"	"	30000	75000	6.8	5600	2.1
4.8	7900	1.45	300.6	"	"	30000	75000	5.7	6700	1.7
4.3	8800	1.3	336.7	"	"	30000	75000	5.1	7400	1.55
3.7	10300	1.1	389.0	"	"	30000	75000	4.4	8600	1.35
3.3	11500	1.0	435.7	"	"	30000	75000	4.0	9500	1.2
2.9	13100	0.88	499.5	"	"	30000	75000	3.5	10900	1.05
6.1	6200	3.0	234.6	BK90Z-../D11MA4	632	49400	120000	7.3	5200	3.6
5.5	6900	2.7	262.5	"	"	49400	120000	6.6	5700	3.2
4.9	7700	2.4	295.6	"	"	49400	120000	5.8	6500	2.8
4.3	8800	2.1	330.7	"	"	49400	120000	5.2	7300	2.5
3.7	10300	1.8	389.1	"	"	49400	120000	4.4	8600	2.2
3.3	11500	1.6	435.3	"	"	49400	120000	4.0	9500	1.95
2.9	13100	1.4	499.2	"	"	49400	120000	3.5	10900	1.7
2.6	14600	1.25	558.5	"	"	49400	120000	3.1	12300	1.5


P = 4.0 кВт



50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
2.3	16600	1.1	637.7	BK90Z-../D11MA4	632	49400	120000	2.7	14100	1.3
2.0	19100	0.97	713.5	"	"	49400	120000	2.4	15900	1.15
1.8	19800	0.93	821.0	BK90G50-../D11MA4	648	49400	120000	2.1	16800	1.1
1.7	21200	0.87	882.3	"	"	49400	120000	2.0	17900	1.05

P = 5.5 кВт

240	200	2.4	6.02	BK40-../D11LA4	102	470	9800	285	169	2.8
190	250	1.95	7.49	"	"	750	10500	230	210	2.3
153	315	1.55	9.31	"	"	1040	11200	184	260	1.9
120	400	1.25	11.86	"	"	1770	12200	145	330	1.5
98	480	1.65	14.50	"	"	4500	14300	118	400	1.95
79	590	1.3	18.05	"	"	4900	15300	95	495	1.6
64	730	1.05	22.44	"	"	5500	16500	77	610	1.3
50	940	0.83	28.59	"	"	6300	17000	60	780	1.0
195	245	3.3	7.29	BK50-../D11LA4	132	620	111000	235	205	4.0
142	340	2.4	10.00	"	"	1220	13200	171	280	2.9
102	460	2.3	13.95	"	"	6100	17400	123	380	2.8
80	590	1.25	17.92	"	"	4600	16800	96	495	1.45
74	630	1.65	19.33	"	"	6900	19200	89	530	2.0
54	870	1.2	26.51	"	"	7800	21200	65	720	1.45
40.5	1160	0.91	35.21	"	"	8700	23100	49	960	1.1
78	670	3.3	18.36	BK60-../D11LA4	142	4000	19900	94	550	4.0
70	750	3.0	20.54	"	"	4400	20600	84	620	3.6
59	890	2.6	24.45	"	"	4850	22000	70	750	3.1
52	1010	2.3	27.36	"	"	5600	23200	63	830	2.8
42.5	1230	1.85	33.78	"	"	6500	25200	51	1020	2.3
38	1380	1.65	37.80	"	"	7300	26500	45.5	1150	2.0
32	1640	1.4	45.05	"	"	8200	28300	38	1380	1.65
28.5	1840	1.25	50.40	"	"	9100	29800	34	1540	1.5
24.5	2100	1.1	58.95	"	"	9900	31500	29.5	1780	1.3
22	2350	0.98	65.95	"	"	10900	33000	26	2000	1.15
18.5	2800	0.82	78.13	"	"	11900	34000	22	2350	0.98
35.5	1470	3.3	40.08	BK70-../D11LA4	221	8300	36300	43	1220	4.0
31.5	1660	3.1	45.59	"	"	9000	37900	38	1380	3.7
26.5	1980	2.6	54.15	"	"	9900	40200	32	1640	3.2
23.5	2200	2.4	61.60	"	"	11500	42800	28	1870	2.8
20.5	2550	2.0	70.23	"	"	12500	44800	24.5	2100	2.5
18	2900	1.8	79.89	"	"	14300	47600	21.5	2400	2.2
16	3250	1.6	90.96	"	"	15300	49900	19	2750	1.9
14	3750	1.4	103.5	"	"	17200	50000	17	3050	1.7
12	4350	1.2	120.2	"	"	18600	50000	14.5	3600	1.45
10.5	5000	1.05	136.7	"	"	20700	50000	13	4000	1.3
9.2	5700	0.91	154.4	"	"	21900	50000	11.5	4550	1.15
8.1	6400	0.81	175.7	"	"	24100	50000	9.8	5300	0.98
16	3250	3.2	91.53	BK80-../D11LA4	336	18300	74200	19	2750	3.8
14	3750	2.8	102.5	"	"	20500	75000	17	3050	3.4
12.5	4200	2.5	117.5	"	"	22300	75000	15	3500	3.0
11	4750	2.2	131.6	"	"	24900	75000	13	4000	2.6
9.3	5600	1.9	153.1	"	"	27200	75000	11.5	4550	2.3
8.3	6300	1.65	171.5	"	"	30000	75000	10	5200	2.0
8.0	6500	1.75	177.6	BK80Z-../D11LA4	378	30000	75000	9.7	5400	2.1
7.2	7200	1.6	198.9	"	"	30000	75000	8.6	6100	1.9
6.3	8300	1.4	226.1	"	"	30000	75000	7.6	6900	1.65
5.7	9200	1.25	253.3	"	"	30000	75000	6.8	7700	1.5
4.8	10900	1.05	300.6	"	"	30000	75000	5.7	9200	1.25



P = 5.5 кВт

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
4.3	12200	0.94	336.7	BK80Z-../D11LA4	378	30000	75000	5.1	10200	1.15
3.7	14100	0.82	389.0	"	"	30000	75000	4.4	11900	0.97
8.2	6400	2.9	174.7	BK90Z-../D11LA4	643	49400	120000	9.8	5300	3.5
7.3	7100	2.6	195.4	"	"	49400	120000	8.8	5900	3.1
6.1	8600	2.2	234.6	"	"	49400	120000	7.3	7100	2.6
5.5	9500	1.95	262.5	"	"	49400	120000	6.6	7900	2.3
4.9	10700	1.75	295.6	"	"	49400	120000	5.8	9000	2.1
4.3	12200	1.5	330.7	"	"	49400	120000	5.2	10100	1.85
3.7	14100	1.3	389.1	"	"	49400	120000	4.4	11900	1.55
3.3	15900	1.15	435.3	"	"	49400	120000	4.0	13100	1.4
2.9	18100	1.0	499.2	"	"	49400	120000	3.5	15000	1.25
2.6	20200	0.92	558.5	"	"	49400	120000	3.1	16900	1.1
2.3	22800	0.81	637.7	"	"	49400	120000	2.7	19400	0.95

P = 7.5 кВт

270	240	3.4	5.26	BK50-../D13MA4	143	130	10700	330	199	4.1
195	335	2.4	7.29	"	"	620	111000	235	280	2.9
142	460	1.75	10.00	"	"	1220	13200	171	385	2.1
102	630	1.65	13.95	"	"	6100	17400	123	520	2.0
80	810	0.9	17.92	"	"	4600	16800	96	670	1.1
74	870	1.2	19.33	"	"	6900	19200	89	720	1.45
54	1190	0.88	26.51	"	"	7800	21200	65	990	1.05
132	540	3.1	10.82	BK60-../D13MA4	155	3200	17000	159	450	3.7
99	720	2.7	14.41	"	"	3650	18600	119	600	3.2
78	910	2.4	18.36	"	"	4000	19900	94	760	2.9
70	1020	2.2	20.54	"	"	4400	20600	84	850	2.6
59	1210	1.9	24.45	"	"	4850	22000	70	1020	2.3
52	1370	1.7	27.36	"	"	5600	23200	63	1130	2.0
42.5	1680	1.35	33.78	"	"	6500	25200	51	1400	1.65
38	1880	1.2	37.80	"	"	7300	26500	45.5	1570	1.45
32	2200	1.05	45.05	"	"	8200	28300	38	1880	1.2
28.5	2500	0.92	50.40	"	"	9100	29800	34	2100	1.1
46	1550	2.9	30.90	BK70-../D13MA4	234	7500	33600	56	1270	3.6
40.5	1760	2.7	35.15	"	"	8000	35000	49	1460	3.2
35.5	2000	2.4	40.08	"	"	8300	36300	43	1660	2.9
31.5	2250	2.3	45.59	"	"	9000	37900	38	1880	2.7
26.5	2700	1.95	54.15	"	"	9900	40200	32	2200	2.4
23.5	3000	1.75	61.60	"	"	11500	42800	28	2550	2.0
20.5	3450	1.5	70.23	"	"	12500	44800	24.5	2900	1.8
18	3950	1.3	79.89	"	"	14300	47600	21.5	3300	1.6
16	4450	1.15	90.96	"	"	15300	49900	19	3750	1.4
14	5100	1.0	103.5	"	"	17200	50000	17	4200	1.25
12	5900	0.88	120.2	"	"	18600	50000	14.5	4900	1.05
27	2650	3.3	53.21	BK80-../D13MA4	348	14800	63100	32.5	2200	4.0
24	2950	3.1	59.60	"	"	15700	65500	29	2450	3.8
20.5	3450	2.8	70.72	"	"	16600	68700	24.5	2900	3.3
18	3950	2.5	79.22	"	"	17600	71300	22	3250	3.1
16	4450	2.3	91.53	"	"	18300	74200	19	3750	2.8
14	5100	2.1	102.5	"	"	20500	75000	17	4200	2.5
12.5	5700	1.85	117.5	"	"	22300	75000	15	4750	2.2
11	6500	1.6	131.6	"	"	24900	75000	13	5500	1.9
9.3	7700	1.35	153.1	"	"	27200	75000	11.5	6200	1.7
8.3	8600	1.2	171.5	"	"	30000	75000	10	7100	1.5
8.0	8900	1.3	177.6	BK80Z-../D13MA4	391	30000	75000	9.7	7300	1.6
7.2	9900	1.15	198.9	"	"	30000	75000	8.6	8300	1.4

P = 7.5 кВт




Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
6.3	11300	1.0	226.1	BK80Z-../D13MA4	391	30000	75000	7.6	9400	1.2
5.7	12500	0.92	253.3	"	"	30000	75000	6.8	10500	1.1
14	5100	3.3	102.0	BK90-../D13MA4	600	36600	107000	17	4200	4.0
12.5	5700	2.9	117.0	"	"	39200	113000	15	4750	3.5
11	6500	2.6	130.9	"	"	42700	119400	13.5	5300	3.2
9.5	7500	2.2	149.5	"	"	45600	120000	11.5	6200	2.7
8.5	8400	2.0	167.2	"	"	49400	120000	10.5	6800	2.5
8.2	8700	2.1	174.7	BK90Z-../D13MA4	656	49400	120000	9.8	7300	2.5
7.3	9800	1.9	195.4	"	"	49400	120000	8.8	8100	2.3
6.1	11700	1.6	234.6	"	"	49400	120000	7.3	9800	1.9
5.5	13000	1.4	262.5	"	"	49400	120000	6.6	10800	1.7
4.9	14600	1.25	295.6	"	"	49400	120000	5.8	12300	1.5
4.3	16600	1.1	330.7	"	"	49400	120000	5.2	13700	1.35
3.7	19300	0.96	389.1	"	"	49400	120000	4.4	16200	1.15
3.3	21700	0.85	435.3	"	"	49400	120000	4.0	17900	1.05

P = 9.5 кВт

270	305	2.7	5.26	BK50-../D13LA4	146	130	10700	330	250	3.2
195	425	1.9	7.29	"	"	620	111000	235	355	2.3
142	580	1.4	10.00	"	"	1220	13200	171	485	1.65
102	800	1.3	13.95	"	"	6100	17400	123	660	1.6
74	1100	0.95	19.33	"	"	6900	19200	89	910	1.15
132	680	2.5	10.82	BK60-../D13LA4	158	3200	17000	159	570	2.9
99	910	2.1	14.41	"	"	3650	18600	119	760	2.5
78	1160	1.9	18.36	"	"	4000	19900	94	960	2.3
70	1290	1.75	20.54	"	"	4400	20600	84	1080	2.1
59	1530	1.5	24.45	"	"	4850	22000	70	1290	1.8
52	1740	1.3	27.36	"	"	5600	23200	63	1440	1.6
42.5	2100	1.1	33.78	"	"	6500	25200	51	1770	1.3
38	2350	0.98	37.80	"	"	7300	26500	45.5	1990	1.15
32	2800	0.82	45.05	"	"	8200	28300	38	2350	0.98
65	1390	2.9	21.88	BK70-../D13LA4	237	6500	30200	79	1140	3.6
58	1560	2.7	24.89	"	"	7000	31500	69	1310	3.3
46	1970	2.3	30.90	"	"	7500	33600	56	1620	2.8
40.5	2200	2.2	35.15	"	"	8000	35000	49	1850	2.6
35.5	2550	1.9	40.08	"	"	8300	36300	43	2100	2.3
31.5	2850	1.8	45.59	"	"	9000	37900	38	2350	2.2
26.5	3400	1.55	54.15	"	"	9900	40200	32	2800	1.85
23.5	3850	1.35	61.60	"	"	11500	42800	28	3200	1.65
20.5	4400	1.2	70.23	"	"	12500	44800	24.5	3700	1.4
18	5000	1.05	79.89	"	"	14300	47600	21.5	4200	1.25
16	5600	0.93	90.96	"	"	15300	49900	19	4750	1.1
14	6400	0.81	103.5	"	"	17200	50000	17	5300	0.98
34	2650	3.1	41.78	BK80-../D13LA4	351	13500	58700	41	2200	3.7
30.5	2950	2.9	46.80	"	"	14300	60900	37	2450	3.5
27	3350	2.6	53.21	"	"	14800	63100	32.5	2750	3.2
24	3750	2.5	59.60	"	"	15700	65500	29	3100	3.0
20.5	4400	2.2	70.72	"	"	16600	68700	24.5	3700	2.6
18	5000	2.0	79.22	"	"	17600	71300	22	4100	2.5
16	5600	1.85	91.53	"	"	18300	74200	19	4750	2.2
14	6400	1.65	102.5	"	"	20500	75000	17	5300	2.0
12.5	7200	1.45	117.5	"	"	22300	75000	15	6000	1.75
11	8200	1.3	131.6	"	"	24900	75000	13	6900	1.5
9.3	9700	1.1	153.1	"	"	27200	75000	11.5	7800	1.35
8.3	10900	0.96	171.5	"	"	30000	75000	10	9000	1.15




P = 9.5 кВт

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
8.0	11300	1.0	177.6	BK80Z-../D13LA4	394	30000	75000	9.7	9300	1.25
7.2	12600	0.91	198.9	"	"	30000	75000	8.6	10500	1.1
6.3	14400	0.8	226.1	"	"	30000	75000	7.6	11900	0.97
16	5600	3.0	91.19	BK90-../D13LA4	603	33300	101000	19	4750	3.5
14	6400	2.6	102.0	"	"	36600	107000	17	5300	3.2
12.5	7200	2.3	117.0	"	"	39200	113000	15	6000	2.8
11	8200	2.0	130.9	"	"	42700	119400	13.5	6700	2.5
9.5	9500	1.75	149.5	"	"	45600	120000	11.5	7800	2.2
8.5	10600	1.6	167.2	"	"	49400	120000	10.5	8600	1.95
8.2	11000	1.7	174.7	BK90Z-../D13LA4	659	49400	120000	9.8	9200	2.0
7.3	12400	1.5	195.4	"	"	49400	120000	8.8	10300	1.8
6.1	14800	1.25	234.6	"	"	49400	120000	7.3	12400	1.5
5.5	16400	1.15	262.5	"	"	49400	120000	6.6	13700	1.35
4.9	18500	1.0	295.6	"	"	49400	120000	5.8	15600	1.2
4.3	21000	0.88	330.7	"	"	49400	120000	5.2	17400	1.05

P = 11 кВт

280	345	2.4	5.26	BK50-../D16MA4	191	130	10700	335	285	2.8
205	470	1.75	7.29	"	"	620	111000	245	390	2.1
146	660	1.25	10.00	"	"	1220	13200	176	540	1.5
105	900	1.15	13.95	"	"	6100	17400	127	740	1.4
76	1240	0.85	19.33	"	"	6900	19200	92	1020	1.05
135	770	2.2	10.82	BK60-../D16MA4	203	3200	17000	163	640	2.6
102	1020	1.9	14.41	"	"	3650	18600	123	850	2.3
80	1310	1.65	18.36	"	"	4000	19900	96	1090	2.0
72	1450	1.55	20.54	"	"	4400	20600	86	1220	1.85
60	1750	1.3	24.45	"	"	4850	22000	72	1450	1.6
54	1940	1.2	27.36	"	"	5600	23200	65	1610	1.45
43.5	2400	0.96	33.78	"	"	6500	25200	53	1980	1.15
39	2650	0.87	37.80	"	"	7300	26500	47	2200	1.05
67	1560	2.6	21.88	BK70-../D16MA4	286	6500	30200	81	1290	3.2
59	1780	2.4	24.89	"	"	7000	31500	71	1470	2.9
47.5	2200	2.1	30.90	"	"	7500	33600	57	1840	2.5
42	2500	1.9	35.15	"	"	8000	35000	51	2050	2.3
36.5	2850	1.7	40.08	"	"	8300	36300	44	2350	2.1
32.5	3200	1.6	45.59	"	"	9000	37900	39	2650	1.95
27	3850	1.35	54.15	"	"	9900	40200	33	3150	1.65
24	4350	1.2	61.60	"	"	11500	42800	29	3600	1.45
21	5000	1.05	70.23	"	"	12500	44800	25.5	4100	1.25
18.5	5600	0.93	79.89	"	"	14300	47600	22.5	4650	1.1
16.5	6300	0.83	90.96	"	"	15300	49900	19.5	5300	0.98
43	2400	3.3	34.22	BK80-../D16MA4	396	12600	55400	52	2000	3.9
35	3000	2.7	41.78	"	"	13500	58700	42.5	2450	3.4
31.5	3300	2.6	46.80	"	"	14300	60900	38	2750	3.1
27.5	3800	2.3	53.21	"	"	14800	63100	33.5	3100	2.9
24.5	4250	2.2	59.60	"	"	15700	65500	30	3500	2.6
21	5000	1.95	70.72	"	"	16600	68700	25	4200	2.3
18.5	5600	1.8	79.22	"	"	17600	71300	22.5	4650	2.2
16	6500	1.6	91.53	"	"	18300	74200	19.5	5300	1.95
14.5	7200	1.45	102.5	"	"	20500	75000	17.5	6000	1.75
12.5	8400	1.25	117.5	"	"	22300	75000	15	7000	1.5
11.5	9100	1.15	131.6	"	"	24900	75000	13.5	7700	1.35
9.6	10900	0.96	153.1	"	"	27200	75000	11.5	9100	1.15
8.6	12200	0.86	171.5	"	"	30000	75000	10.5	10000	1.05
8.3	12600	0.91	177.6	BK80Z-../D16MA4	439	30000	75000	10	10500	1.1

P = 11 кВт




Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
7.4	14100	0.82	198.9	BK80Z-../D16MA4	439	30000	75000	8.9	11800	0.97
19	5500	3.1	77.51	BK90-../D16MA4	649	30300	94400	23	4550	3.7
16.5	6300	2.7	91.19	"	"	33300	101000	19.5	5300	3.2
14.5	7200	2.3	102.0	"	"	36600	107000	17.5	6000	2.8
12.5	8400	2.0	117.0	"	"	39200	113000	15.5	6700	2.5
11.5	9100	1.85	130.9	"	"	42700	119400	13.5	7700	2.2
9.8	10700	1.55	149.5	"	"	45600	120000	12	8700	1.95
8.8	11900	1.4	167.2	"	"	49400	120000	11	9500	1.75
8.4	12500	1.5	174.7	BK90Z-../D16MA4	708	49400	120000	10.5	10000	1.85
7.5	14000	1.3	195.4	"	"	49400	120000	9.1	11500	1.6
6.3	16600	1.1	234.6	"	"	49400	120000	7.6	13800	1.35
5.6	18700	0.99	262.5	"	"	49400	120000	6.8	15400	1.2
5.0	21000	0.88	295.6	"	"	49400	120000	6.0	17500	1.05

P = 15 кВт

280	470	1.75	5.26	BK50-../D16LA4	204	130	10700	335	390	2.1
205	640	1.25	7.29	"	"	620	111000	245	530	1.55
146	900	0.9	10.00	"	"	1220	13200	176	740	1.1
105	1220	0.86	13.95	"	"	6100	17400	127	1010	1.05
135	1060	1.6	10.82	BK60-../D16LA4	216	3200	17000	163	870	1.95
102	1400	1.4	14.41	"	"	3650	18600	123	1160	1.65
80	1790	1.2	18.36	"	"	4000	19900	96	1490	1.45
72	1980	1.15	20.54	"	"	4400	20600	86	1660	1.35
60	2350	0.98	24.45	"	"	4850	22000	72	1980	1.15
54	2650	0.87	27.36	"	"	5600	23200	65	2200	1.05
67	2100	1.95	21.88	BK70-../D16LA4	299	6500	30200	81	1760	2.3
59	2400	1.8	24.89	"	"	7000	31500	71	2000	2.1
47.5	3000	1.5	30.90	"	"	7500	33600	57	2500	1.8
42	3400	1.4	35.15	"	"	8000	35000	51	2800	1.7
36.5	3900	1.25	40.08	"	"	8300	36300	44	3250	1.5
32.5	4400	1.15	45.59	"	"	9000	37900	39	3650	1.4
27	5300	0.98	54.15	"	"	9900	40200	33	4300	1.2
24	5900	0.88	61.60	"	"	11500	42800	29	4900	1.05
48	2950	2.5	30.56	BK80-../D16LA4	409	11900	53400	58	2450	3.1
43	3300	2.4	34.22	"	"	12600	55400	52	2750	2.8
35	4050	2.0	41.78	"	"	13500	58700	42.5	3350	2.5
31.5	4500	1.9	46.80	"	"	14300	60900	38	3750	2.3
27.5	5200	1.7	53.21	"	"	14800	63100	33.5	4250	2.1
24.5	5800	1.6	59.60	"	"	15700	65500	30	4750	1.95
21	6800	1.4	70.72	"	"	16600	68700	25	5700	1.7
18.5	7700	1.3	79.22	"	"	17600	71300	22.5	6300	1.6
16	8900	1.15	91.53	"	"	18300	74200	19.5	7300	1.4
14.5	9800	1.05	102.5	"	"	20500	75000	17.5	8100	1.3
12.5	11400	0.92	117.5	"	"	22300	75000	15	9500	1.1
11.5	12400	0.85	131.6	"	"	24900	75000	13.5	10600	0.99
27	5300	3.0	54.98	BK90-../D16LA4	662	24000	81000	32.5	4400	3.7
24	5900	2.8	61.52	"	"	25500	84600	29	4900	3.4
21.5	6600	2.5	69.27	"	"	27200	88900	25.5	5600	3.0
19	7500	2.2	77.51	"	"	30300	94400	23	6200	2.7
16.5	8600	1.95	91.19	"	"	33300	101000	19.5	7300	2.3
14.5	9800	1.7	102.0	"	"	36600	107000	17.5	8100	2.1
12.5	11400	1.45	117.0	"	"	39200	113000	15.5	9200	1.85
11.5	12400	1.35	130.9	"	"	42700	119400	13.5	10600	1.6
9.8	14600	1.15	149.5	"	"	45600	120000	12	11900	1.4

P = 15 кВт



50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
8.8	16200	1.05	167.2	BK90-../D16LA4	662	49400	120000	11	13000	1.3
8.4	17000	1.1	174.7	BK90Z-../D16LA4	721	49400	120000	10.5	13600	1.35
7.5	19100	0.97	195.4	"	"	49400	120000	9.1	15700	1.2
6.3	22700	0.81	234.6	"	"	49400	120000	7.6	18800	0.98


P = 18.5 кВт

280	580	1.4	5.26	BK50-../D16XA4	214	130	10700	335	485	1.65
205	790	1.05	7.29	"	"	620	111000	245	660	1.25
135	1300	1.3	10.82	BK60-../D16XA4	226	3200	17000	163	1080	1.55
102	1730	1.1	14.41	"	"	3650	18600	123	1430	1.35
80	2200	0.99	18.36	"	"	4000	19900	96	1840	1.2
72	2450	0.92	20.54	"	"	4400	20600	86	2050	1.1
67	2600	1.55	21.88	BK70-../D16XA4	309	6500	30200	81	2150	1.9
59	2950	1.45	24.89	"	"	7000	31500	71	2450	1.75
47.5	3700	1.2	30.90	"	"	7500	33600	57	3050	1.5
42	4200	1.15	35.15	"	"	8000	35000	51	3450	1.35
36.5	4800	1.0	40.08	"	"	8300	36300	44	4000	1.2
32.5	5400	0.95	45.59	"	"	9000	37900	39	4500	1.15
27	6500	0.8	54.15	"	"	9900	40200	33	5300	0.98
48	3650	2.1	30.56	BK80-../D16XA4	419	11900	53400	58	3000	2.5
43	4100	1.9	34.22	"	"	12600	55400	52	3350	2.3
35	5000	1.65	41.78	"	"	13500	58700	42.5	4150	2.0
31.5	5600	1.55	46.80	"	"	14300	60900	38	4600	1.85
27.5	6400	1.4	53.21	"	"	14800	63100	33.5	5200	1.7
24.5	7200	1.3	59.60	"	"	15700	65500	30	5800	1.6
21	8400	1.15	70.72	"	"	16600	68700	25	7000	1.4
18.5	9500	1.05	79.22	"	"	17600	71300	22.5	7800	1.3
16	11000	0.95	91.53	"	"	18300	74200	19.5	9000	1.15
14.5	12100	0.87	102.5	"	"	20500	75000	17.5	10000	1.05
36	4900	3.0	40.94	BK90-../D16XA4	672	21400	73100	43	4100	3.6
32	5500	2.8	45.80	"	"	22700	76300	38.5	4550	3.4
27	6500	2.5	54.98	"	"	24000	81000	32.5	5400	3.0
24	7300	2.3	61.52	"	"	25500	84600	29	6000	2.8
21.5	8200	2.0	69.27	"	"	27200	88900	25.5	6900	2.4
19	9200	1.85	77.51	"	"	30300	94400	23	7600	2.2
16.5	10700	1.55	91.19	"	"	33300	101000	19.5	9000	1.85
14.5	12100	1.4	102.0	"	"	36600	107000	17.5	10000	1.7
12.5	14100	1.2	117.0	"	"	39200	113000	15.5	11300	1.5
11.5	15300	1.1	130.9	"	"	42700	119400	13.5	13000	1.3
9.8	18000	0.93	149.5	"	"	45600	120000	12	14700	1.15
8.8	20000	0.84	167.2	"	"	49400	120000	11	16000	1.05
8.4	21000	0.88	174.7	BK90Z-../D16XA4	731	49400	120000	10.5	16800	1.1

P = 22 кВт

97	2150	1.45	15.16	BK70-../D18LA4	366	5600	25800	117	1790	1.7
85	2450	1.45	17.24	"	"	6500	29200	103	2000	1.75
67	3100	1.3	21.88	"	"	6500	30200	81	2550	1.6
59	3550	1.2	24.89	"	"	7000	31500	71	2950	1.45
47.5	4400	1.05	30.90	"	"	7500	33600	57	3650	1.25
42	5000	0.95	35.15	"	"	8000	35000	51	4100	1.15
36.5	5700	0.86	40.08	"	"	8300	36300	44	4750	1.05
32.5	6400	0.8	45.59	"	"	9000	37900	39	5300	0.97

P = 22 кВт




Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/мин	M ₂ , Нм	f _B						n ₂ , 1/мин	M ₂ , Нм	f _B
92	2250	2.1	15.88	БК80-../D18LA4	480	8400	38600	111	1890	2.5
83	2500	2.1	17.79	"	"	9400	42100	99	2100	2.5
66	3150	2.2	22.19	"	"	10500	48500	80	2600	2.6
59	3550	2.0	24.85	"	"	11200	50400	71	2950	2.4
48	4350	1.7	30.56	"	"	11900	53400	58	3600	2.1
43	4850	1.6	34.22	"	"	12600	55400	52	4000	1.95
35	6000	1.35	41.78	"	"	13500	58700	42.5	4900	1.7
31.5	6600	1.3	46.80	"	"	14300	60900	38	5500	1.55
27.5	7600	1.15	53.21	"	"	14800	63100	33.5	6200	1.45
24.5	8500	1.1	59.60	"	"	15700	65500	30	7000	1.3
21	10000	0.96	70.72	"	"	16600	68700	25	8400	1.15
18.5	11300	0.89	79.22	"	"	17600	71300	22.5	9300	1.1
48	4350	3.1	30.47	БК90-../D18LA4	735	19100	65900	58	3600	3.8
43	4850	2.9	34.09	"	"	20300	68800	52	4000	3.5
36	5800	2.5	40.94	"	"	21400	73100	43	4850	3.0
32	6500	2.4	45.80	"	"	22700	76300	38.5	5400	2.9
27	7700	2.1	54.98	"	"	24000	81000	32.5	6400	2.5
24	8700	1.95	61.52	"	"	25500	84600	29	7200	2.3
21.5	9700	1.75	69.27	"	"	27200	88900	25.5	8200	2.0
19	11000	1.55	77.51	"	"	30300	94400	23	9100	1.85
16.5	12700	1.3	91.19	"	"	33300	101000	19.5	10700	1.55
14.5	14400	1.15	102.0	"	"	36600	107000	17.5	12000	1.4
12.5	16800	1.0	117.0	"	"	39200	113000	15.5	13500	1.25
11.5	18200	0.92	130.9	"	"	42700	119400	13.5	15500	1.1

P = 30 кВт

97	2950	1.05	15.16	БК70-../D18XA4	384	5600	25800	117	2400	1.3
85	3350	1.05	17.24	"	"	6500	29200	103	2750	1.25
67	4250	0.96	21.88	"	"	6500	30200	81	3500	1.15
59	4850	0.88	24.89	"	"	7000	31500	71	4000	1.05
92	3100	1.55	15.88	БК80-../D18XA4	498	8400	38600	111	2550	1.9
83	3450	1.5	17.79	"	"	9400	42100	99	2850	1.85
66	4300	1.6	22.19	"	"	10500	48500	80	3550	1.9
59	4850	1.45	24.85	"	"	11200	50400	71	4000	1.75
48	5900	1.25	30.56	"	"	11900	53400	58	4900	1.55
43	6600	1.2	34.22	"	"	12600	55400	52	5500	1.4
35	8100	1.0	41.78	"	"	13500	58700	42.5	6700	1.25
31.5	9000	0.95	46.80	"	"	14300	60900	38	7500	1.15
27.5	10400	0.85	53.21	"	"	14800	63100	33.5	8500	1.05
24.5	11600	0.8	59.60	"	"	15700	65500	30	9500	0.97
81	3500	3.3	18.07	БК90-../D18XA4	753	15600	54400	98	2900	4.0
73	3900	3.1	20.21	"	"	16600	56700	88	3250	3.7
66	4300	2.9	22.29	"	"	16900	59100	79	3600	3.4
59	4850	2.6	24.94	"	"	18000	61700	71	4000	3.2
48	5900	2.3	30.47	"	"	19100	65900	58	4900	2.8
43	6600	2.1	34.09	"	"	20300	68800	52	5500	2.6
36	7900	1.85	40.94	"	"	21400	73100	43	6600	2.2
32	8900	1.75	45.80	"	"	22700	76300	38.5	7400	2.1
27	10600	1.5	54.98	"	"	24000	81000	32.5	8800	1.85
24	11900	1.4	61.52	"	"	25500	84600	29	9800	1.7
21.5	13300	1.25	69.27	"	"	27200	88900	25.5	11200	1.5
19	15000	1.1	77.51	"	"	30300	94400	23	12400	1.35
16.5	17300	0.97	91.19	"	"	33300	101000	19.5	14600	1.15
14.5	19700	0.85	102.0	"	"	36600	107000	17.5	16300	1.05

P = 37 кВт



Danfoss

50 Гц			i	Тип	m, кг	F _{RN} , Н	F _{RV} , Н	60 Гц		
n ₂ , 1/МИН	M ₂ , Нм	f _B						n ₂ , 1/МИН	M ₂ , Нм	f _B
92	3800	1.25	15.88	БК80-...-К/DNF22SB4	713	8400	38600	111	3150	1.5
83	4250	1.25	17.79	"	"	9400	42100	99	3550	1.5
66	5300	1.3	22.19	"	"	10500	48500	80	4400	1.55
59	5900	1.2	24.85	"	"	11200	50400	71	4950	1.45
48	7300	1.05	30.56	"	"	11900	53400	58	6000	1.25
81	4350	2.6	18.07	БК90-...-К/DNF22SB4	966	15600	54400	98	3600	3.2
73	4800	2.5	20.21	"	"	16600	56700	88	4000	3.0
66	5300	2.3	22.29	"	"	16900	59100	79	4450	2.8
59	5900	2.2	24.94	"	"	18000	61700	71	4950	2.6
48	7300	1.85	30.47	"	"	19100	65900	58	6000	2.3
43	8200	1.7	34.09	"	"	20300	68800	52	6700	2.1
36	9800	1.5	40.94	"	"	21400	73100	43	8200	1.8
32	11000	1.4	45.80	"	"	22700	76300	38.5	9100	1.7
27	13000	1.25	54.98	"	"	24000	81000	32.5	10800	1.5
24	14700	1.15	61.52	"	"	25500	84600	29	12100	1.4
21.5	16400	1.0	69.27	"	"	27200	88900	25.5	13800	1.2

P = 45 кВт

92	4650	1.05	15.88	БК80-...-К/DNF22MB4	743	8400	38600	111	3850	1.25
83	5100	1.05	17.79	"	"	9400	42100	99	4300	1.2
66	6500	1.05	22.19	"	"	10500	48500	80	5300	1.3
81	5300	2.2	18.07	БК90-...-К/DNF22MB4	996	15600	54400	98	4350	2.6
73	5800	2.1	20.21	"	"	16600	56700	88	4850	2.5
66	6500	1.9	22.29	"	"	16900	59100	79	5400	2.3
59	7200	1.8	24.94	"	"	18000	61700	71	6000	2.1
48	8900	1.5	30.47	"	"	19100	65900	58	7400	1.85
43	9900	1.4	34.09	"	"	20300	68800	52	8200	1.7
36	11900	1.25	40.94	"	"	21400	73100	43	9900	1.5
32	13400	1.15	45.80	"	"	22700	76300	38.5	11100	1.4
27	15900	1.0	54.98	"	"	24000	81000	32.5	13200	1.2