

## 2.8 Dane techniczne

## 2.8 Technical data


## 2.8 Технические параметры

| T   | n <sub>1</sub> = 1400 |        |                       | TC - TF              |                      |     |       | TA                    |         |
|-----|-----------------------|--------|-----------------------|----------------------|----------------------|-----|-------|-----------------------|---------|
|     | in                    | ir     | n <sub>2</sub><br>rpm | T <sub>2</sub><br>Nm | P <sub>1</sub><br>kW | FS' | IEC   | T <sub>2M</sub><br>Nm | P<br>kW |
| 56B | 8                     | 8.06   | 174                   | 94                   | 1.8                  | 1.2 | 56    | 110                   | 2.1     |
|     | 10                    | 10.17  | 138                   | 119                  | 1.8                  | 1.0 | 63    | 120                   | 1.8     |
|     | 12.5                  | 12.31  | 114                   | 120                  | 1.5                  | 1.1 | (B5)  | 130                   | 1.6     |
|     | 16                    | 15.00  | 93                    | 107                  | 1.1                  | 1.3 | 71    | 140                   | 1.4     |
|     | 20                    | 20.33  | 69                    | 119                  | 0.9                  | 1.2 | 80    | 140                   | 1.1     |
|     | 25                    | 24.62  | 57                    | 120                  | 0.75                 | 1.2 | 90    | 140                   | 0.90    |
|     | 31.5                  | 30.00  | 47                    | 107                  | 0.55                 | 1.3 | (B5)  | 140                   | 0.70    |
|     | 40                    | 39.38  | 36                    | 140                  | 0.55                 | 1.0 | (B14) | 140                   | 0.55    |
|     | 50                    | 48.00  | 29                    | 115                  | 0.37                 | 1.2 | TF    | 140                   | 0.45    |
| 56C | 40                    | 40.28  | 35                    | 95                   | 0.37                 | 1.4 | 56    | 135                   | 0.53    |
|     | 50                    | 50.83  | 28                    | 119                  | 0.37                 | 1.2 | 63    | 140                   | 0.43    |
|     | 63                    | 61.54  | 23                    | 98                   | 0.25                 | 1.4 | (B5)  | 140                   | 0.36    |
|     | 80                    | 75.00  | 19                    | 119                  | 0.25                 | 1.2 | 71    | 145                   | 0.30    |
|     | 100                   | 101.67 | 14                    | 116                  | 0.18                 | 1.2 | 80    | 145                   | 0.22    |
|     | 125                   | 123.08 | 11                    | 141                  | 0.18                 | 1.0 | 90    | 145                   | 0.19    |
|     | 160                   | 150.00 | 9                     | 124                  | 0.13                 | 1.2 | (B5)  | 145                   | 0.15    |
|     | 200                   | 196.92 | 7                     | 112                  | 0.09                 | 1.3 | (B14) | 145                   | 0.10    |
|     | 250                   | 240.00 | 6                     | 137                  | 0.09                 | 1.1 | TF    | 150                   | 0.10    |
| 63B | 8                     | 7.94   | 176                   | 93                   | 1.8                  | 1.7 | 56    | 155                   | 3.0     |
|     | 10                    | 10.18  | 138                   | 119                  | 1.8                  | 1.4 | 63    | 170                   | 2.6     |
|     | 12.5                  | 12.50  | 112                   | 146                  | 1.8                  | 1.3 | (B5)  | 185                   | 2.3     |
|     | 16                    | 15.88  | 88                    | 185                  | 1.8                  | 1.1 | 71    | 200                   | 1.9     |
|     | 20                    | 20.36  | 69                    | 198                  | 1.5                  | 1.0 | 80    | 200                   | 1.5     |
|     | 25                    | 25.00  | 56                    | 178                  | 1.1                  | 1.1 | 90    | 200                   | 1.2     |
|     | 31.5                  | 31.00  | 45                    | 181                  | 0.9                  | 1.1 | (B5)  | 200                   | 1.0     |
|     | 40                    | 40.00  | 35                    | 194                  | 0.75                 | 1.0 | (B14) | 200                   | 0.80    |
|     | 50                    | 49.60  | 28                    | 177                  | 0.55                 | 1.1 | TF    | 200                   | 0.60    |
| 63C | 40                    | 39.71  | 35                    | 189                  | 0.75                 | 1.1 | 56    | 200                   | 0.79    |
|     | 50                    | 50.89  | 28                    | 178                  | 0.55                 | 1.2 | 63    | 210                   | 0.65    |
|     | 63                    | 62.50  | 22                    | 147                  | 0.37                 | 1.4 | (B5)  | 210                   | 0.53    |
|     | 80                    | 79.41  | 18                    | 186                  | 0.37                 | 1.1 | 71    | 210                   | 0.42    |
|     | 100                   | 101.79 | 14                    | 161                  | 0.25                 | 1.3 | 80    | 210                   | 0.33    |
|     | 125                   | 125.00 | 11                    | 198                  | 0.25                 | 1.1 | 90    | 210                   | 0.26    |
|     | 160                   | 155.00 | 9                     | 177                  | 0.18                 | 1.2 | (B5)  | 210                   | 0.21    |
|     | 200                   | 200.00 | 7                     | 165                  | 0.13                 | 1.3 | (B14) | 210                   | 0.17    |
|     | 250                   | 248.00 | 6                     | 205                  | 0.13                 | 1.0 | TF    | 210                   | 0.13    |
| 71B | 10                    | 10.25  | 137                   | 120                  | 1.8                  | 1.9 | 56    | 230                   | 3.5     |
|     | 12.5                  | 13.05  | 107                   | 152                  | 1.8                  | 1.6 | 63    | 240                   | 2.8     |
|     | 16                    | 15.63  | 90                    | 182                  | 1.8                  | 1.4 | 71    | 250                   | 2.5     |
|     | 20                    | 19.64  | 71                    | 229                  | 1.8                  | 1.3 | 80    | 290                   | 2.3     |
|     | 25                    | 24.99  | 56                    | 243                  | 1.5                  | 1.2 | 90    | 280                   | 1.7     |
|     | 31.5                  | 29.95  | 47                    | 213                  | 1.1                  | 1.2 | (B5)  | 260                   | 1.3     |
|     | 40                    | 38.73  | 36                    | 226                  | 0.9                  | 1.1 | TC-TF | 240                   | 1.0     |
|     | 50                    | 50.18  | 28                    | 244                  | 0.75                 | 1.1 | 80    | 260                   | 0.80    |
|     | 63                    | 60.13  | 23                    | 214                  | 0.55                 | 1.2 | (B14) | 260                   | 0.70    |
| 71C | 80                    | 77.76  | 18                    | 186                  | 0.37                 | 1.3 | TC    | 240                   | 0.50    |

| T    | n <sub>1</sub> = 1400 |        |                       | TC - TF              |                      |     |       | TA                    |         |
|------|-----------------------|--------|-----------------------|----------------------|----------------------|-----|-------|-----------------------|---------|
|      | in                    | ir     | n <sub>2</sub><br>rpm | T <sub>2</sub><br>Nm | P <sub>1</sub><br>kW | FS' | IEC   | T <sub>2M</sub><br>Nm | P<br>kW |
| 90B  | 5*                    | 4.56   | 307                   | 118                  | 4                    | 3.2 | 56    | 380                   | 12.8    |
|      | 6.3*                  | 6.26   | 224                   | 162                  | 4                    | 2.5 | 63    | 405                   | 10.0    |
|      | 10                    | 10.25  | 137                   | 266                  | 4                    | 1.8 | 71    | 480                   | 7.2     |
|      | 12.5                  | 13.05  | 107                   | 338                  | 4                    | 1.6 | 80    | 530                   | 6.3     |
|      | 16                    | 15.63  | 90                    | 405                  | 4                    | 1.4 | 90    | 550                   | 5.4     |
|      | 20                    | 19.64  | 71                    | 509                  | 4                    | 1.2 | 100   | 620                   | 4.9     |
|      | 25                    | 24.99  | 56                    | 486                  | 3                    | 1.3 | (B5)  | 630                   | 3.9     |
|      | 31.5                  | 29.95  | 47                    | 427                  | 2.2                  | 1.3 | 90•   | 560                   | 2.9     |
|      | 40                    | 38.73  | 36                    | 452                  | 1.8                  | 1.1 | (B14) | 500                   | 2.0     |
| 90C  | 50                    | 50.18  | 28                    | 488                  | 1.5                  | 1.1 | TC    | 550                   | 1.7     |
|      | 63                    | 60.13  | 23                    | 429                  | 1.1                  | 1.3 |       | 570                   | 1.5     |
|      | 80                    | 77.76  | 18                    | 454                  | 0.9                  | 1.1 |       | 505                   | 1.0     |
| 80C  | 50                    | 52.18  | 27                    | 596                  | 1.8                  | 1.1 |       | 660                   | 2.0     |
|      | 63                    | 62.53  | 22                    | 595                  | 1.5                  | 1.1 |       | 680                   | 1.7     |
|      | 80                    | 79.58  | 18                    | 555                  | 1.1                  | 1.3 | 63    | 710                   | 1.4     |
|      | 100                   | 99.97  | 14                    | 698                  | 1.1                  | 1.1 | 71    | 740                   | 1.2     |
|      | 125                   | 119.78 | 12                    | 684                  | 0.9                  | 1.1 | 80    | 740                   | 1.0     |
|      | 160                   | 152.45 | 9                     | 532                  | 0.55                 | 1.3 | 90    | 680                   | 0.70    |
|      | 200                   | 182.67 | 8                     | 637                  | 0.55                 | 1.1 | (B5)  | 700                   | 0.60    |
|      | 250                   | 240.51 | 6                     | 565                  | 0.37                 | 1.3 | TC-TF | 750                   | 0.49    |
|      | 315                   | 306.11 | 5                     | 719                  | 0.37                 | 1.0 | 80    | 740                   | 0.38    |
| 112B | 400                   | 366.78 | 4                     | 582                  | 0.25                 | 1.2 | TC    | 700                   | 0.30    |
|      | 500                   | 474.35 | 3                     | 542                  | 0.18                 | 1.2 |       | 660                   | 0.22    |
|      | 630                   | 613.46 | 2                     | 506                  | 0.13                 | 1.2 |       | 620                   | 0.16    |
| 112C | 5*                    | 4.86   | 288                   | 290                  | 9.2                  | 1.5 |       | 440                   | 14.0    |
|      | 10                    | 10.25  | 137                   | 611                  | 9.2                  | 1.5 |       | 920                   | 13.9    |
|      | 12.5                  | 13.05  | 107                   | 778                  | 9.2                  | 1.3 |       | 1000                  | 11.8    |
|      | 16                    | 15.63  | 90                    | 932                  | 9.2                  | 1.2 | 80    | 1100                  | 10.9    |
|      | 20                    | 19.64  | 71                    | 1171                 | 9.2                  | 1.0 | 90    | 1190                  | 9.4     |
|      | 25                    | 24.99  | 56                    | 1215                 | 7.5                  | 1.1 | 100   | 1190                  | 9.4     |
|      | 31.5                  | 29.95  | 47                    | 1067                 | 5.5                  | 1.1 | 112   | 1280                  | 7.9     |
|      | 40                    | 38.73  | 36                    | 1004                 | 4                    | 1.0 | 125   | 1220                  | 6.3     |
|      | 50                    | 50.18  | 28                    | 976                  | 3                    | 1.1 | (B5)  | 1050                  | 4.2     |
| 100C | 63                    | 60.13  | 23                    | 857                  | 2.2                  | 1.4 | TC-TF | 1070                  | 3.3     |
|      | 80                    | 77.76  | 18                    | 907                  | 1.8                  | 1.2 |       | 1240                  | 3.2     |
|      | 50                    | 52.18  | 27                    | 993                  | 3                    | 1.3 |       | 1080                  | 2.1     |
|      | 63                    | 62.53  | 22                    | 1190                 | 3                    | 1.1 |       | 1300                  | 3.9     |
|      | 80                    | 79.58  | 18                    | 1111                 | 2.2                  | 1.3 | 71    | 1350                  | 3.4     |
|      | 100                   | 99.97  | 14                    | 1395                 | 2.2                  | 1.1 | 80    | 1410                  | 2.8     |
|      | 125                   | 119.78 | 12                    | 1368                 | 1.8                  | 1.1 | 90    | 1470                  | 2.3     |
|      | 160                   | 152.45 | 9                     | 1064                 | 1.1                  | 1.3 | 100   | 1480                  | 1.9     |
|      | 200                   | 182.67 | 8                     | 1275                 | 1.1                  | 1.1 | 112   | 1360                  | 1.4     |

• Kolnierze kwadratowe / Square flanges / Квадратные фланцы

\* Specjalne przełożenia / Special ratios / Специальное передаточное отношение



# 2.8 Dane techniczne

# 2.8 Technical data

# 2.8 Технические параметры

| T    | n <sub>1</sub> = 1400 |        |                       | TC - TF              |                      |     |      | TA                    |         |
|------|-----------------------|--------|-----------------------|----------------------|----------------------|-----|------|-----------------------|---------|
|      | in                    | ir     | n <sub>2</sub><br>rpm | T <sub>2</sub><br>Nm | P <sub>1</sub><br>kW | FS' | IEC  | T <sub>2M</sub><br>Nm | P<br>kW |
| 140B | 7*                    | 6.88   | 203                   | 983                  | 22                   | 1.4 |      | 1350                  | 30.2    |
|      | 10                    | 10.25  | 137                   | 1461                 | 22                   | 1.3 |      | 1850                  | 27.9    |
|      | 12.5                  | 13.05  | 107                   | 1860                 | 22                   | 1.1 |      | 2050                  | 24.3    |
|      | 16                    | 15.63  | 90                    | 1874                 | 18.5                 | 1.2 | 80   | 2200                  | 21.7    |
|      | 20                    | 19.64  | 71                    | 2354                 | 18.5                 | 1.0 | 90   | 2400                  | 18.9    |
|      | 25                    | 24.99  | 56                    | 2429                 | 15                   | 1.0 | 100  | 2540                  | 15.7    |
|      | 31.5                  | 29.95  | 47                    | 2135                 | 11                   | 1.1 | 112  | 2300                  | 11.9    |
|      | 40                    | 38.73  | 36                    | 1882                 | 7.5                  | 1.2 | 132  | 2210                  | 8.8     |
|      | 50                    | 50.18  | 28                    | 1789                 | 5.5                  | 1.2 | 160  | 2120                  | 6.5     |
|      | 63                    | 60.13  | 23                    | 2143                 | 5.5                  | 1.1 | 180  | 2350                  | 6.0     |
| 125C | 80                    | 77.76  | 18                    | 2016                 | 4                    | 1.1 | (B5) | 2250                  | 4.5     |
|      | 50                    | 52.18  | 27                    | 2483                 | 7.5                  | 1.1 |      | 2650                  | 8.0     |
|      | 63                    | 62.53  | 22                    | 2182                 | 5.5                  | 1.3 |      | 2760                  | 7.0     |
|      | 80                    | 79.58  | 18                    | 2777                 | 5.5                  | 1.0 |      | 2880                  | 5.7     |
|      | 100                   | 99.97  | 14                    | 2537                 | 4                    | 1.2 | 80   | 3000                  | 4.7     |
|      | 125                   | 119.78 | 12                    | 2280                 | 3                    | 1.3 | 90   | 3000                  | 4.0     |
|      | 160                   | 152.45 | 9                     | 2128                 | 2.2                  | 1.3 | 100  | 2720                  | 2.8     |
|      | 200                   | 182.67 | 8                     | 2549                 | 2.2                  | 1.1 | 112  | 2800                  | 2.4     |
|      | 250                   | 240.51 | 6                     | 2746                 | 1.8                  | 1.1 | 132  | 3050                  | 2.0     |
|      | 315                   | 306.11 | 5                     | 2913                 | 1.5                  | 1.0 | (B5) | 2960                  | 1.5     |
| 180B | 400                   | 366.78 | 4                     | 2560                 | 1.1                  | 1.1 |      | 2800                  | 1.2     |
|      | 500                   | 474.35 | 3                     | 2257                 | 0.75                 | 1.2 |      | 2640                  | 0.90    |
|      | 630                   | 613.46 | 2                     | 2140                 | 0.55                 | 1.2 |      | 2550                  | 0.70    |
|      | 10                    | 10.25  | 137                   | 1993                 | 30                   | 2.0 |      | 3900                  | 58.7    |
|      | 12.5                  | 13.05  | 107                   | 2536                 | 30                   | 1.7 |      | 4300                  | 50.9    |
|      | 16                    | 15.63  | 90                    | 3039                 | 30                   | 1.5 | 100  | 4500                  | 44.4    |
|      | 20                    | 19.64  | 71                    | 3818                 | 30                   | 1.3 | 112  | 5100                  | 40.1    |
|      | 25                    | 24.99  | 56                    | 4859                 | 30                   | 1.1 | 132  | 5230                  | 32.3    |
|      | 31.5                  | 29.95  | 47                    | 4269                 | 22                   | 1.1 | 160  | 4680                  | 24.1    |
|      | 40                    | 38.73  | 36                    | 3764                 | 15                   | 1.1 | 180  | 4300                  | 17.1    |
| 160C | 50                    | 50.18  | 28                    | 3577                 | 11                   | 1.2 | 200  | 4300                  | 13.2    |
|      | 63                    | 60.13  | 23                    | 4286                 | 11                   | 1.1 | (B5) | 4780                  | 12.3    |
|      | 80                    | 77.76  | 18                    | 3779                 | 7.5                  | 1.2 |      | 4380                  | 8.7     |
|      | 50                    | 52.18  | 27                    | 4966                 | 15                   | 1.0 |      | 5130                  | 15.5    |
|      | 63                    | 62.53  | 22                    | 4363                 | 11                   | 1.2 |      | 5350                  | 13.5    |
|      | 80                    | 79.58  | 18                    | 4644                 | 9.2                  | 1.2 |      | 5570                  | 11.0    |
|      | 100                   | 99.97  | 14                    | 4756                 | 7.5                  | 1.2 | 80   | 5800                  | 9.2     |
|      | 125                   | 119.78 | 12                    | 5699                 | 7.5                  | 1.0 | 90   | 5800                  | 7.6     |
|      | 160                   | 152.45 | 9                     | 5319                 | 5.5                  | 1.0 | 100  | 5470                  | 5.7     |
|      | 200                   | 182.67 | 8                     | 4635                 | 4                    | 1.2 | 112  | 5600                  | 4.8     |
| 180C | 250                   | 240.51 | 6                     | 4577                 | 3                    | 1.3 | 132  | 5890                  | 3.3     |
|      | 315                   | 306.11 | 5                     | 5826                 | 3                    | 1.0 | 160  | 5920                  | 3.0     |
|      | 400                   | 366.78 | 4                     | 5119                 | 2.2                  | 1.1 | 180  | 5600                  | 2.4     |
|      | 500                   | 474.35 | 3                     | 4514                 | 1.5                  | 1.2 | (B5) | 5280                  | 1.8     |
|      | 630                   | 613.46 | 2                     | 4281                 | 1.1                  | 1.2 |      | 4960                  | 1.3     |
|      | 50                    | 52.18  | 27                    | 4966                 | 15                   | 1.0 |      | 5130                  | 15.5    |
|      | 63                    | 62.53  | 22                    | 4363                 | 11                   | 1.2 |      | 5350                  | 13.5    |
|      | 80                    | 79.58  | 18                    | 4644                 | 9.2                  | 1.2 |      | 5570                  | 11.0    |

| T    | n <sub>1</sub> = 1400 |        |                       | TC - TF              |                      |     |      | TA                    |         |
|------|-----------------------|--------|-----------------------|----------------------|----------------------|-----|------|-----------------------|---------|
|      | in                    | ir     | n <sub>2</sub><br>rpm | T <sub>2</sub><br>Nm | P <sub>1</sub><br>kW | FS' | IEC  | T <sub>2M</sub><br>Nm | P<br>kW |
| 200B | 8                     | 8.14   | 172                   | 1582                 | 30                   | 3.2 |      | 5000                  | 94.8    |
|      | 10                    | 10.43  | 134                   | 2028                 | 30                   | 2.7 |      | 5500                  | 81.4    |
|      | 12.5                  | 12.60  | 111                   | 2449                 | 30                   | 2.4 |      | 6000                  | 73.5    |
|      | 16                    | 15.63  | 90                    | 3039                 | 30                   | 2.1 | 112  | 6500                  | 64.2    |
|      | 20                    | 17.65  | 79                    | 3432                 | 30                   | 2.1 | 132  | 6500                  | 64.2    |
|      | 25                    | 24.14  | 58                    | 4692                 | 30                   | 1.5 | 160  | 7100                  | 62.1    |
|      | 31.5                  | 29.95  | 47                    | 5822                 | 30                   | 1.2 | 180  | 7150                  | 45.7    |
|      | 40                    | 33.82  | 41                    | 6575                 | 30                   | 1.1 | 200  | 7250                  | 37.4    |
|      | 50                    | 47.93  | 29                    | 6833                 | 22                   | 1.1 | (B5) | 7300                  | 33.3    |
|      | 63                    | 54.13  | 26                    | 6489                 | 18.5                 | 1.1 |      | 7400                  | 23.8    |
| 180C | 50                    | 53.11  | 26                    | 6234                 | 18.5                 | 1.2 |      | 7400                  | 21.1    |
|      | 63                    | 63.64  | 22                    | 6056                 | 15                   | 1.2 |      | 7240                  | 21.5    |
|      | 80                    | 76.85  | 18                    | 7313                 | 15                   | 1.0 | 80   | 7280                  | 18.0    |
|      | 100                   | 99.39  | 14                    | 6936                 | 11                   | 1.1 | 90   | 7420                  | 15.2    |
|      | 125                   | 122.88 | 11                    | 7172                 | 9.2                  | 1.0 | 100  | 7500                  | 11.9    |
|      | 160                   | 147.23 | 10                    | 7005                 | 7.5                  | 1.1 | 112  | 7500                  | 9.6     |
|      | 200                   | 190.41 | 7                     | 6644                 | 5.5                  | 1.1 | 132  | 7550                  | 8.1     |
|      | 250                   | 246.73 | 6                     | 6261                 | 4                    | 1.2 | 160  | 7600                  | 6.3     |
|      | 315                   | 295.63 | 5                     | 7502                 | 4                    | 1.0 | 180  | 7650                  | 4.9     |
|      | 400                   | 382.33 | 4                     | 7276                 | 3                    | 1.1 | (B5) | 7700                  | 4.1     |
| 225B | 8                     | 8.44   | 166                   | 2461                 | 45                   | 3.0 |      | 7950                  | 3.3     |
|      | 10                    | 10.13  | 138                   | 2955                 | 45                   | 2.8 |      | 7500                  | 137.1   |
|      | 12.5                  | 12.45  | 112                   | 3630                 | 45                   | 2.5 | 132  | 8300                  | 126.4   |
|      | 16                    | 15.93  | 88                    | 4644                 | 45                   | 2.2 | 160  | 9100                  | 112.8   |
|      | 20                    | 19.13  | 73                    | 5577                 | 45                   | 1.9 | 180  | 10000                 | 96.9    |
|      | 25                    | 23.49  | 60                    | 6850                 | 45                   | 1.6 | 200  | 10700                 | 86.3    |
|      | 31.5                  | 30.29  | 46                    | 8832                 | 45                   | 1.3 | 225  | 11000                 | 72.3    |
|      | 40                    | 37.09  | 38                    | 8892                 | 37                   | 1.2 | (B5) | 11000                 | 72.3    |
|      | 40                    | 42.62  | 33                    | 8110                 | 30                   | 1.3 | TF   | 11100                 | 56.6    |
|      | 50                    | 51.18  | 27                    | 9740                 | 30                   | 1.1 |      | 10800                 | 44.9    |
| 200C | 63                    | 62.86  | 22                    | 8772                 | 22                   | 1.3 |      | 10900                 | 40.3    |
|      | 80                    | 76.97  | 18                    | 10742                | 22                   | 1.0 | 100  | 11000                 | 33.9    |
|      | 100                   | 98.04  | 14                    | 9330                 | 15                   | 1.2 | 112  | 11350                 | 28.5    |
|      | 125                   | 120.41 | 12                    | 11459                | 15                   | 1.0 | 132  | 11350                 | 28.5    |
|      | 160                   | 147.45 | 9                     | 10290                | 11                   | 1.1 | 160  | 11050                 | 22.6    |
|      | 200                   | 196.87 | 7                     | 9367                 | 7.5                  | 1.2 | 180  | 11200                 | 18.0    |
|      | 250                   | 241.79 | 6                     | 11504                | 7.5                  | 1.0 | 200  | 11200                 | 18.0    |
|      | 315                   | 296.07 | 5                     | 10330                | 5.5                  | 1.1 | (B5) | 11500                 | 15.1    |
| 200C | 400                   | 366.78 | 4                     | 5119                 | 2.2                  | 1.1 |      | 11200                 | 12.0    |
|      | 500                   | 474.35 | 3                     | 4514                 | 1.5                  | 1.2 |      | 11400                 | 9.1     |
| 200C | 630                   | 613.46 | 2                     | 4281                 | 1.1                  | 1.2 |      | 11700                 | 7.6     |
|      | 630                   | 613.46 | 2                     | 4281                 | 1.1                  | 1.2 |      | 11850                 | 6.3     |

• Kolnierze kwadratowe / Square flanges / Квадратные фланцы

\* Specjalne przełożenie / Special ratio / Специальное передаточное отношение