



3.7 Эксплуатационные характеристики мотор - редукторов

0.09 kW					
		$n_1 = 860 \text{ min}^{-1}$		63B 6	

44	19.5	18	14.0	63	63B 6
31	27.5	25	10.5	63	63B 6
28	31.2	28	9.3	63	63B 6
24	35.8	32	8.1	63	63B 6
19.3	44.6	40	6.5	63	63B 6
16.4	52.4	47	5.5	63	63B 6
12.5	69.0	62	4.2	63	63B 6
10.8	79.5	71	3.6	63	63B 6
9.5	90.6	82	3.1	63	63B 6
8.3	103.8	93	2.7	63	63B 6
6.7	129.3	116	2.2	63	63B 6
5.7	151.9	137	1.9	63	63B 6
4.8	179.6	162	3.2	71	63B 6
4.4	193.6	174	3.0	71	63B 6
4.3	200.1	180	1.4	63	63B 6
3.9	220.8	199	2.6	71	63B 6
3.5	243.3	219	1.2	63	63B 6
3.4	253.4	228	2.3	71	63B 6
3.1	280.4	252	1.1	63	63B 6
3.0	286.0	257	2.0	71	63B 6
2.5	342.9	308	1.7	71	63B 6
2.5	346.4	312	0.9	63	63B 6
2.2	387.0	348	1.5	71	63B 6

0.13 kW					
		$n_1 = 1360 \text{ min}^{-1}$		63A 4	
		$n_1 = 860 \text{ min}^{-1}$		63C 6	

57	23.7	20	12.3	63	63A 4
50	27.5	23	10.6	63	63A 4
44	30.6	25	18.3	71	63A 4
44	31.2	26	9.3	63	63A 4
38	35.8	29	8.5	63	63A 4
31	44.6	37	6.8	63	63A 4
26	52.4	43	5.8	63	63A 4
19.7	69.0	57	4.4	63	63A 4
17.1	79.5	65	3.8	63	63A 4
15.0	90.6	74	3.1	63	63A 4
13.1	103.8	85	2.8	63	63A 4
10.5	129.3	106	2.3	63	63A 4
9.0	151.9	125	2.0	63	63A 4
8.1	168.0	136	3.3	71	63A 4
7.6	179.6	148	3.1	71	63A 4
7.0	193.6	159	2.9	71	63A 4
6.8	200.1	164	1.5	63	63A 4
6.5	209.4	172	2.7	71	63A 4
6.2	220.8	181	2.5	71	63A 4
5.6	243.3	200	1.3	63	63A 4
5.4	253.4	208	2.2	71	63A 4
4.8	280.4	230	1.1	63	63A 4
4.6	298.8	245	1.9	71	63A 4
4.0	342.9	282	1.6	71	63A 4
3.9	346.4	285	0.9	63	63A 4
3.5	387.0	318	1.4	71	63A 4
2.9	298.8	388	1.4	71	63C 6
2.5	342.9	445	1.2	71	63C 6
2.2	387.0	503	1.0	71	63C 6

0.18 kW					
		$n_1 = 1370 \text{ min}^{-1}$		63B 4	
		$n_1 = 870 \text{ min}^{-1}$		71A 6	

92	14.8	17	13.1	63	63B 4
80	17.2	19	11.4	63	63B 4
70	19.5	22	10.4	63	63B 4
58	23.7	27	9.0	63	63B 4
50	27.5	31	7.7	63	63B 4
44	31.2	35	6.8	63	63B 4
38	35.8	40	6.2	63	63B 4
31	44.6	50	5.0	63	63B 4
26	52.4	59	4.2	63	63B 4
19.9	69.0	78	3.2	63	63B 4
17.2	79.5	90	2.8	63	63B 4
15.1	90.6	102	2.2	63	63B 4
13.2	103.8	117	2.0	63	63B 4
11.1	123.5	139	3.3	71	63B 4
10.6	129.3	146	1.6	63	63B 4
9.6	143.1	162	2.8	71	63B 4
9.0	151.9	172	1.4	63	63B 4
8.9	154.8	175	2.6	71	63B 4
8.2	168.0	190	2.4	71	63B 4
7.6	179.6	203	2.3	71	63B 4
7.1	193.6	219	2.1	71	63B 4
6.8	200.1	226	1.1	63	63B 4
6.5	209.4	236	1.9	71	63B 4
6.2	220.8	249	1.8	71	63B 4
5.6	243.3	275	0.9	63	63B 4
5.4	253.4	286	1.6	71	63B 4
4.9	280.4	317	0.8	63	63B 4
4.8	286.0	323	1.4	71	63B 4
4.6	298.8	337	1.4	71	63B 4
4.0	342.9	387	1.2	71	63B 4
3.5	387.0	437	1.1	71	63B 4
3.0	294.9	524	2.0	90	71A 6
2.9	298.8	531	1.0	71	71A 6
2.8	309.6	551	1.9	90	71A 6
2.6	338.1	601	1.7	90	71A 6
2.5	342.9	610	0.9	71	71A 6
2.2	390.0	694	1.5	90	71A 6
1.7	501.6	912	3.0	125	71A 6
1.6	555.7	1010	2.7	125	71A 6

0.22 kW					
		$n_1 = 1400 \text{ min}^{-1}$		63C 4	

122	11.5	15	12.3	63	63C 4
105	13.3	18	12.3	63	63C 4
94	14.8	20	11.0	63	63C 4
82	17.2	23	9.5	63	63C 4
72	19.5	26	8.7	63	63C 4
59	23.7	32	7.5	63	63C 4
51	27.5	37	6.5	63	63C 4
45	31.2	42	5.7	63	63C 4
39	35.8	48	5.2	63	63C 4
31	44.6	60	4.2	63	63C 4
27	52.4	71	3.5	63	63C 4
20	69.0	93	2.7	63	63C 4
17.6	79.5	107	2.3	63	63C 4
15.4	90.6	122	1.9	63	63C 4

0.22 kW					
		$n_1 = 1400 \text{ min}^{-1}$		63C 4	

13.5	103.8	140	1.7	63	63C 4
11.3	123.5	167	2.8	71	63C 4
10.8	129.3	175	1.4	63	63C 4
9.8	143.1	193	2.4	71	63C 4
9.2	151.9	205	1.2	63	63C 4
9.0	154.8	209	2.2	71	63C 4
8.3	168.0	227	2.0	71	63C 4
7.8	179.6	243	1.9	71	63C 4
7.2	193.6	262	1.8	71	63C 4
7.0	200.1	270	0.9	63	63C 4
6.7	209.4	283	1.6	71	63C 4
6.3	220.8	298	1.5	71	63C 4
5.5	253.4	343	1.3	71	63C 4
4.9	286.0	386	1.2	71	63C 4
4.7	298.8	404	1.1	71	63C 4
4.1	342.9	463	1.0	71	63C 4
3.6	387.0	523	0.9	71	63C 4
2.5	555.7	767	3.5	125	63C 4

0.25 kW					
		$n_1 = 1370 \text{ min}^{-1}$		71A 4	
		$n_1 = 870 \text{ min}^{-1}$		71B 6	

173	7.9	12	13.7	63	71A 4
133	10.3	16	11.5	63	71A 4
119	11.5	18	10.6	63	71A 4
103	13.3	21	10.6	63	71A 4
92	14.8	23	9.5	63	71A 4
80	17.2	27	8.2	63	71A 4
70	19.5	31	7.5	63	71A 4
58	23.7	37	6.4	63	71A 4
50	27.5	43	5.6	63	71A 4
44	31.2	49	4.9	63	71A 4
38	35.8	56	4.5	63	71A 4
31	44.6	70	3.6	63	71A 4
26	52.4	82	3.0	63	71A 4
19.9	69.0	108	2.3	63	71A 4
17.2	79.5	125	2.0	63	71A 4
15.7	87.4	137	3.4	71	71A 4
15.1	90.6	142	1.6	63	71A 4
13.9	98.6	155	3.0	71	71A 4
13.2	103.8	163	1.4	63	71A 4
12.7	107.6	169	2.7	71	71A 4
11.1	123.5	194	2.4	71	71A 4
10.6	129.3	203	1.2	63	71A 4
9.0	151.9	238	1.0	63	71A 4
8.9	154.8	243	1.9	71	71A 4
8.2	168.0	263	1.7	71	71A 4
7.6	179.6	282	1.6	71	71A 4
6.5	209.4	328	1.4	71	71A 4
6.4	212.6	333	2.7	90	71A 4
6.2	220.8	346	1.3	71	71A 4
5.9	234.1	367	2.5	90	71A 4
5.4	253.4	397	1.2	71	71A 4
5.1	268.3	421	2.2	90	71A 4
4.8	286.0	449	1.0	71	71A 4
4.6	294.9	463	2.0	90	71A 4
4.6	298.8	469	1.0	71	71A 4
4.4	309.6	486	1.9	90	71A 4



HIGH TECH *line*



n_2 min ⁻¹	ir	T2 Nm	FS'	OM-OC ROC	
----------------------------	----	----------	-----	--------------	--

1.8 kW				$n_1=2770 \text{ min}^{-1}$ $n_1=1400 \text{ min}^{-1}$ $n_1=940 \text{ min}^{-1}$	80D 2 90LB 4 100B 6
---------------	--	--	--	--	---------------------------

17.4	80.7	892	1.0	90	90LB 4
16.9	82.9	956	2.8	125	90LB 4
16.4	85.4	944	1.9	112	90LB 4
15.6	89.8	1036	2.6	125	90LB 4
15.1	92.5	1022	0.9	90	90LB 4
14.9	93.9	1038	1.7	112	90LB 4
14.3	97.8	1129	2.4	125	90LB 4
13.6	102.8	1136	1.5	112	90LB 4
13.1	107.1	1237	2.2	125	90LB 4
12.6	110.9	1226	1.4	112	90LB 4
11.2	125.2	1384	1.3	112	90LB 4
11.0	126.7	1431	2.8	140	90LB 4
11.0	126.8	1433	2.0	125	90LB 4
10.3	135.6	1499	1.2	112	90LB 4
10.2	137.4	1552	2.6	140	90LB 4
10.2	137.5	1554	1.8	125	90LB 4
9.0	154.8	1711	1.0	112	90LB 4
8.5	163.8	1850	2.2	140	90LB 4
8.5	163.9	1852	1.5	125	90LB 4
8.4	166.0	1835	1.0	112	90LB 4
8.4	166.8	1884	3.0	160	90LB 4
7.8	180.2	2036	2.0	140	90LB 4
7.8	180.4	2038	1.4	125	90LB 4
7.6	183.6	2073	2.7	160	90LB 4
7.2	194.9	2154	0.8	112	90LB 4
6.2	225.2	2544	1.5	140	90LB 4
6.2	225.4	2546	1.1	125	90LB 4
6.1	229.3	2591	2.1	160	90LB 4
6.0	232.7	2629	2.9	180	90LB 4
5.2	271.2	3063	1.2	140	90LB 4
5.2	271.4	3066	0.9	125	90LB 4
5.1	276.2	3120	1.7	160	90LB 4
5.0	280.1	3164	2.4	180	90LB 4
4.3	327.8	3703	2.1	180	90LB 4
4.1	344.7	3894	2.8	200	90LB 4
3.9	359.4	4060	0.9	140	90LB 4
3.8	366.1	4135	1.3	160	90LB 4
3.2	432.3	4884	1.1	160	90LB 4
3.2	438.9	4958	2.2	200	90LB 4
3.1	457.2	5165	1.5	180	90LB 4
2.7	527.8	5962	1.8	200	90LB 4
2.5	557.2	6294	1.2	180	90LB 4
2.4	576.8	6516	0.8	160	90LB 4
2.1	457.2	7692	1.0	180	100B 6
2.0	479.9	8074	1.4	200	100B 6
1.7	557.2	9375	0.8	180	100B 6
1.6	584.3	9831	1.1	200	100B 6

2.2 kW				$n_1=2840 \text{ min}^{-1}$ $n_1=1410 \text{ min}^{-1}$ $n_1=940 \text{ min}^{-1}$	90L 2 100A 4 100BL 6
---------------	--	--	--	--	----------------------------

414	6.9	46	4.8	71	90L 2
359	7.9	53	2.7	63	90L 2
338	8.4	56	4.5	71	90L 2
286	9.9	66	3.9	71	90L 2
276	10.3	68	2.2	63	90L 2
250	11.4	76	3.7	71	90L 2

n_2 min ⁻¹	ir	T2 Nm	FS'	OM-OC ROC	
----------------------------	----	----------	-----	--------------	--

2.2 kW				$n_1=2840 \text{ min}^{-1}$ $n_1=1410 \text{ min}^{-1}$ $n_1=940 \text{ min}^{-1}$	90L 2 100A 4 100BL 6
---------------	--	--	--	--	----------------------------

248	11.5	76	2.0	63	90L 2
214	13.3	88	2.0	63	90L 2
206	6.9	92	2.9	71	100A 4
192	14.8	99	1.8	63	90L 2
178	7.9	106	1.6	63	100A 4
168	8.4	113	2.7	71	100A 4
142	9.9	133	2.4	71	100A 4
137	10.3	138	1.3	63	100A 4
124	11.4	153	2.2	71	100A 4
123	11.5	154	1.2	63	100A 4
109	13.0	174	3.1	90	100A 4
106	13.3	178	1.2	63	100A 4
101	13.9	187	2.1	71	100A 4
101	14.0	188	3.1	90	100A 4
95	14.8	199	1.1	63	100A 4
86	16.5	221	1.8	71	100A 4
82	17.2	230	1.0	63	100A 4
79	17.7	238	3.2	90	100A 4
75	18.7	251	1.6	71	100A 4
72	19.5	262	0.9	63	100A 4
70	20.1	270	2.9	90	100A 4
61	22.9	308	1.4	71	100A 4
61	23.0	308	2.7	90	100A 4
55	25.7	344	2.6	90	100A 4
52	27.1	363	1.3	71	100A 4
49	28.8	387	2.4	90	100A 4
46	30.6	410	1.1	71	100A 4
43	32.5	436	2.1	90	100A 4
38	36.9	495	1.8	90	100A 4
38	37.1	497	0.9	71	100A 4
33	42.2	565	1.6	90	100A 4
33	42.6	571	0.8	71	100A 4
31	45.2	606	1.5	90	100A 4
30	46.8	627	2.8	112	100A 4
27	52.4	702	1.3	90	100A 4
26	53.4	716	2.4	112	100A 4
25	57.2	768	2.3	112	100A 4
24	59.5	797	1.1	90	100A 4
22	64.6	866	2.0	112	100A 4
19.8	71.2	997	2.8	125	100A 4
19.2	73.3	983	0.9	90	100A 4
18.3	77.0	1033	1.7	112	100A 4
17.5	80.7	1082	0.8	90	100A 4
17.4	81.2	1137	3.3	140	100A 4
17.0	82.9	1161	2.3	125	100A 4
16.5	85.4	1146	1.5	112	100A 4
15.7	89.8	1258	2.1	125	100A 4
15.0	93.9	1259	1.4	112	100A 4
14.5	97.0	1359	2.8	140	100A 4
13.7	102.8	1378	1.3	112	100A 4
13.2	107.1	1500	2.5	140	100A 4
13.2	107.1	1501	1.8	125	100A 4
12.7	110.9	1487	1.2	112	100A 4
11.3	125.2	1679	1.0	112	100A 4
11.1	126.7	1737	2.3	140	100A 4
11.1	126.8	1739	1.6	125	100A 4
10.4	135.6	1819	1.0	112	100A 4
10.3	137.4	1884	2.1	140	100A 4
10.3	137.5	1886	1.5	125	100A 4

n_2 min ⁻¹	ir	T2 Nm	FS'	OM-OC ROC	
----------------------------	----	----------	-----	--------------	--

2.2 kW				$n_1=2840 \text{ min}^{-1}$ $n_1=1410 \text{ min}^{-1}$ $n_1=940 \text{ min}^{-1}$	90L 2 100A 4 100BL 6
---------------	--	--	--	--	----------------------------

10.1	140.0	1919	2.9	160	100A 4
9.1	154.8	2076	0.8	112	100A 4
8.6	163.8	2245	1.8	140	100A 4
8.6	163.9	2247	1.2	125	100A 4
8.5	166.0	2227	0.8	112	100A 4
7.8	180.2	2470	1.6	140	100A 4
7.8	180.4	2473	1.1	125	100A 4
7.7	183.6	2516	2.2	160	100A 4
6.8	206.8	2834	1.3	140	100A 4
6.8	207.0	2837	1.0	125	100A 4
6.7	210.6	2887	1.9	160	100A 4
6.3	225.2	3087	1.2	140	100A 4
6.3	225.4	3090	0.9	125	100A 4
6.1	229.3	3144	1.7	160	100A 4
6.1	232.7	3190	2.4	180	100A 4
5.3	267.3	3664	2.9	200	100A 4
5.2	271.2	3717	1.0	140	100A 4
5.1	276.2	3786	1.4	160	100A 4
5.0	280.1	3840	2.0	180	100A 4
4.3	327.8	4493	1.7	180	100A 4
4.1	344.7	4726	2.3	200	100A 4
3.9	366.1	5018	1.1	160	100A 4
3.3	432.3	5926	0.9	160	100A 4
3.2	438.9	6016	1.8	200	100A 4
3.1	457.2	6267	1.2	180	100A 4
2.5	557.2	7638	1.0	180	100A 4
2.4	584.3	8011	1.3	200	100A 4
2.1	457.2	9401	0.8	180	100BL 6
2.0	479.9	9868	1.1	200	100BL 6
1.8	527.8	10852	1.0	200	100BL 6
1.6	584.3	12016	0.9	200	100BL 6

3 kW				$n_1=2840 \text{ min}^{-1}$ $n_1=1420 \text{ min}^{-1}$ $n_1=940 \text{ min}^{-1}$	90L 2 100B 4 112B 6
-------------	--	--	--	--	---------------------------

414	6.9	62	3.5	71	90LB 2
359	7.9	72	1.9	63*	90LB 2
338	8.4	76	3.3	71	90LB 2
286	9.9	90	2.9	71	90LB 2
276	10.3	93	1.6	63*	90LB 2
250	11.4	103	2.7	71	90LB 2
248	11.5	104	1.5	63*	90LB 2
214	13.3	121	1.5	63*	90LB 2
207	6.9	125	2.2	71	100B 4
197	7.2	131	3.3	90	100B 4
192	14.8	135	1.3	63*	90LB 2
180	7.9	144	1.2	63*	100B 4
169	8.4	153	2.0	71	100B 4
157	9.0	164	2.7	90	100B 4
143	9.9	180	1.8	71	100B 4
140	10.1	184	2.7	90	100B 4
138	10.3	187	1.0	63*	100B 4
125	11.4	207	1.6	71	100B 4
124	11.5	208	2.5	90	100B 4
124	11.5	208	0.9	63*	100B 4
109	13.0	236	2.3	90	100B 4
107	13.3	241	0.9	63*	100B 4





ПРОМЫШЛЕННЫЕ РЕДУКТОРЫ

HIGH TECH line

ПРОМЫШЛЕННЫЕ РЕДУКТОРЫ

ПРОМЫШЛЕННЫЕ РЕДУКТОРЫ

n_2 min ⁻¹	ir	T2 Nm	FS'	OM-OC ROC	
----------------------------	----	----------	-----	--------------	--

22 kW $n_1 = 2925 \text{ min}^{-1}$ $n_2 = 1460 \text{ min}^{-1}$ $n_3 = 975 \text{ min}^{-1}$ 180M 2
180L 4
200L 6

60	24.4	3302	1.1	140	180L 4
59	24.9	3364	1.5	160	180L 4
57	25.5	3448	3.0	200	180L 4
57	25.8	3487	2.2	180	180L 4
53	27.6	3727	2.0	180	180L 4
52	28.0	3783	1.0	140	180L 4
51	28.5	3853	1.3	160	180L 4
50	29.0	3926	2.7	200	180L 4
49	30.0	4063	0.9	140	180L 4
48	30.6	4138	1.3	160	180L 4
47	31.1	4203	2.5	200	180L 4
46	31.7	4286	1.7	180	180L 4
43	34.1	4615	1.7	180	180L 4
42	35.0	4728	0.8	140	180L 4
41	35.6	4816	1.1	160	180L 4
41	35.9	4854	2.2	200	180L 4
38	38.6	5223	1.0	160	180L 4
38	38.7	5241	2.1	200	180L 4
37	40.0	5405	1.4	180	180L 4
34	43.5	5884	1.3	180	180L 4
32	45.7	6179	1.7	200	180L 4
32	46.0	6224	0.9	160	180L 4
29	50.0	6757	1.7	200	180L 4
29	50.6	6849	0.8	160	180L 4
28	52.4	7083	1.1	180	180L 4
27	54.9	7431	1.5	200	180L 4
26	55.9	7565	1.1	180	180L 4
24	61.0	8248	1.0	180	180L 4
24	62.1	8395	1.3	200	180L 4
21	68.1	9206	1.2	200	180L 4
19.8	73.8	9985	0.8	180	180L 4
19.4	75.1	10164	1.1	200	180L 4
17.7	54.9	11128	1.0	200	200L 6
15.7	62.1	12571	0.9	200	200L 6
14.3	68.1	13785	0.8	200	200L 6

n_2 min ⁻¹	ir	T2 Nm	FS'	OM-OC ROC	
----------------------------	----	----------	-----	--------------	--

30 kW $n_1 = 2945 \text{ min}^{-1}$ $n_2 = 1465 \text{ min}^{-1}$ 200L 2
200L 4

73	20.1	3696	1.9	180	200L 4
73	20.2	3713	1.0	140	200L 4
71	20.6	3781	1.3	160	200L 4
69	21.3	3907	2.6	200	200L 4
65	22.5	4145	2.5	200	200L 4
65	22.7	4172	1.8	180	200L 4
64	22.9	4206	0.9	140	200L 4
63	23.3	4284	1.2	160	200L 4
60	24.4	4488	0.8	140	200L 4
59	24.9	4571	1.1	160	200L 4
57	25.5	4686	2.2	200	200L 4
57	25.8	4739	1.6	180	200L 4
53	27.6	5064	1.5	180	200L 4
51	28.5	5236	1.0	160	200L 4
50	29.0	5336	2.0	200	200L 4
48	30.6	5624	0.9	160	200L 4
47	31.1	5712	1.8	200	200L 4
46	31.7	5825	1.3	180	200L 4
43	34.1	6272	1.2	180	200L 4
41	35.6	6545	0.8	160	200L 4
41	35.9	6597	1.6	200	200L 4
38	38.7	7122	1.5	200	200L 4
37	40.0	7345	1.0	180	200L 4
34	43.5	7997	1.0	180	200L 4
32	45.7	8398	1.3	200	200L 4
29	50.0	9183	1.2	200	200L 4
28	52.4	9626	0.8	180	200L 4
27	54.9	10099	1.1	200	200L 4
24	62.1	11409	1.0	200	200L 4
22	68.1	12511	0.9	200	200L 4
19.5	75.1	13812	0.8	200	200L 4

n_2 min ⁻¹	ir	T2 Nm	FS'	OM-OC ROC	
----------------------------	----	----------	-----	--------------	--

37 kW $n_1 = 2950 \text{ min}^{-1}$ $n_2 = 1475 \text{ min}^{-1}$ 200L 2
225S 4

65	22.5	5078	2.1	200	225S 4
65	22.7	5111	1.5	180	225S 4
63	23.3	5248	1.0	160	225S 4
59	24.9	5599	0.9	160	225S 4
58	25.5	5741	1.8	200	225S 4
57	25.8	5805	1.3	180	225S 4
54	27.6	6204	1.2	180	225S 4
52	28.5	6414	0.8	160	225S 4
51	29.0	6536	1.6	200	225S 4
47	31.1	6997	1.5	200	225S 4
47	31.7	7135	1.1	180	225S 4
43	34.1	7683	1.0	180	225S 4
41	35.9	8081	1.3	200	225S 4
38	38.7	8724	1.2	200	225S 4
37	40.0	8997	0.9	180	225S 4
32	45.7	10287	1.0	200	225S 4
30	50.0	11249	1.0	200	225S 4
27	54.9	12371	0.9	200	225S 4
24	62.1	13976	0.8	200	225S 4

30 kW $n_1 = 2945 \text{ min}^{-1}$ $n_2 = 1465 \text{ min}^{-1}$ 200L 2
200L 4

294	10.0	915	2.3	125	200L 2
242	12.1	1111	3.0	140	200L 2
238	12.4	1131	2.1	125	200L 2
184	16.0	1461	2.3	140	200L 2
181	16.3	1488	1.6	125	200L 2
149	9.8	1806	1.8	140	200L 4
146	10.0	1840	2.7	160	200L 4
146	10.0	1840	1.2	125	200L 4
121	12.1	2233	1.5	140	200L 4
118	12.4	2274	2.2	160	200L 4
118	12.4	2274	1.1	125	200L 4
114	12.9	2369	3.0	180	200L 4
92	16.0	2938	1.2	140	200L 4
90	16.0	2941	2.4	180	200L 4
90	16.3	2992	0.8	125	200L 4
90	16.3	2992	1.7	160	200L 4
84	35.0	3197	1.1	140	200L 2

37 kW $n_1 = 2950 \text{ min}^{-1}$ $n_2 = 1475 \text{ min}^{-1}$ 200L 2
225S 4

300	9.8	1106	2.8	140	200L 2
295	10.0	1127	1.9	125*	200L 2
243	12.1	1368	2.4	140	200L 2
238	12.4	1393	1.7	125*	200L 2
185	16.0	1799	1.9	140	200L 2
181	16.3	1833	1.3	125*	200L 2
181	16.3	1833	2.6	160	200L 2
153	9.7	2177	3.0	180	225S 4
150	9.8	2213	1.5	140	225S 4
147	10.0	2253	2.2	160	225S 4
121	12.1	2735	1.3	140	225S 4
119	12.4	2786	1.8	160	225S 4
114	12.9	2902	2.4	180	225S 4
97	15.2	3431	2.9	200	225S 4
92	16.0	3598	1.0	140	225S 4
92	16.0	3603	1.9	180	225S 4
91	16.3	3665	1.4	160	225S 4
84	35.0	3936	0.9	140	200L 2
73	20.1	4528	1.6	180	225S 4
72	20.6	4632	1.1	160	225S 4
69	21.3	4786	2.1	200	225S 4

45 kW $n_1 = 2945 \text{ min}^{-1}$ $n_2 = 1475 \text{ min}^{-1}$ 225M 2
225M 4

300	9.8	1348	2.3	140*	225M 2
294	10.0	1373	3.4	160	225M 2
242	12.1	1666	2.0	140*	225M 2
238	12.4	1697	2.8	160	225M 2
184	16.0	2192	1.5	140*	225M 2
181	16.3	2233	2.1	160	225M 2
153	9.7	2647	2.5	180	225M 4
150	9.8	2691	1.2	140*	225M 4
147	10.0	2741	1.8	160	225M 4
130	22.7	3113	2.3	180	225M 2
121	12.1	3327	1.0	140*	225M 4
119	12.4	3388	2.9	200	225M 4
119	12.4	3388	1.5	160	225M 4
114	12.9	3530	2.0	180	225M 4
97	15.2	4172	2.4	200	225M 4
92	16.0	4382	1.6	180	225M 4
91	16.3	4458	1.1	160	225M 4
83	35.6	4884	1.1	160	225M 2
73	20.1	5507	1.3	180	225M 4
72	20.6	5634	0.9	160	225M 4
69	21.3	5821	1.7	200	225M 4
65	22.5	6175	1.7	200	225M 4
65	22.7	6216	1.2	180	225M 4
63	23.3	6382	0.8	160	225M 4
58	25.5	6982	1.5	200	225M 4
57	25.8	7060	1.1	180	225M 4
54	27.6	7545	1.0	180	225M 4
51	29.0	7949	1.3	200	225M 4
47	31.1	8510	1.2	200	225M 4
47	31.7	8678	0.9	180	225M 4
43	34.1	9344	0.8	180	225M 4
41	35.9	9828	1.1	200	225M 4
38	38.7	10611	1.0	200	225M 4



ПРОМЫШЛЕННЫЕ РЕДУКТОРЫ

HIGH TECH *line* ПРОМЫШЛЕННЫЕ РЕДУКТОРЫ

ПРОМЫШЛЕННЫЕ РЕДУКТОРЫ



n_2 min ⁻¹	ir	T2 Nm	FS'	OM-OC ROC	
----------------------------	----	----------	-----	--------------	--

n_2 min ⁻¹	ir	T2 Nm	FS'	OM-OC ROC	
----------------------------	----	----------	-----	--------------	--

n_2 min ⁻¹	ir	T2 Nm	FS'	OM-OC ROC	
----------------------------	----	----------	-----	--------------	--

45 kW	$n_1 = 2945 \text{ min}^{-1}$	225M 2
	$n_1 = 1475 \text{ min}^{-1}$	225M 4

75 kW	$n_1 = 2975 \text{ min}^{-1}$	280S 2
	$n_1 = 1470 \text{ min}^{-1}$	250M 4

90 kW	$n_1 = 2975 \text{ min}^{-1}$	280M 2
	$n_1 = 1480 \text{ min}^{-1}$	280M 4

32	45.7	12511	0.9	200	225M 4
30	50.0	13681	0.8	200	225M 4

308	9.7	2188	2.8	180*	280S 2
295	10.1	2284	4.1	200	280S 2
231	12.9	2917	2.3	180*	280S 2
195	15.2	3448	2.7	200	280S 2
186	16.0	3621	1.8	180*	280S 2
152	9.7	4427	1.5	180*	250M 4
146	10.1	4622	2.1	200	250M 4
119	12.4	5665	1.7	200	250M 4
114	12.9	5903	1.2	180*	250M 4
96	15.2	6978	1.4	200	250M 4
92	16.0	7328	1.0	180*	250M 4
69	21.3	9734	1.0	200	250M 4
65	22.5	10327	1.0	200	250M 4
58	25.5	11676	0.9	200	250M 4

308	9.7	2625	2.4	180*	280M 2
295	10.1	2741	3.4	200*	280M 2
241	12.4	3359	2.8	200*	280M 2
231	12.9	3500	1.9	180*	280M 2
195	15.2	4137	2.3	200*	280M 2
186	16.0	4345	1.5	180*	280M 2
153	9.7	5277	1.2	180*	280M 4
147	10.1	5509	1.8	200*	280M 4
120	12.4	6752	1.5	200*	280M 4
115	12.9	7036	1.0	180*	280M 4
97	15.2	8317	1.2	200*	280M 4
93	16.0	8734	0.8	180*	280M 4
70	21.3	11602	0.9	200*	280M 4
66	22.5	12309	0.9	200*	280M 4

55 kW	$n_1 = 2950 \text{ min}^{-1}$	250M 2
	$n_1 = 1475 \text{ min}^{-1}$	250M 4

305	9.7	1618	3.8	180	250M 2
229	12.9	2157	3.1	180	250M 2
184	16.0	2678	2.5	180	250M 2
153	9.7	3236	2.0	180	250M 4
148	10.0	3347	1.5	160	250M 4
146	10.1	3378	2.9	200	250M 4
119	12.4	4150	1.2	160	250M 4
119	12.4	4140	2.4	200	250M 4
114	12.9	4314	1.6	180	250M 4
97	15.2	5100	1.9	200	250M 4
92	16.0	5356	1.3	180	250M 4
90	16.3	5456	0.9	160*	250M 4
73	20.1	6730	1.1	180	250M 4
69	21.3	7114	1.4	200	250M 4
65	22.5	7548	1.4	200	250M 4
65	22.7	7597	1.0	180	250M 4
58	25.5	8533	1.2	200	250M 4
57	25.8	8629	0.9	180	250M 4
54	27.6	9222	0.8	180	250M 4
51	29.0	9716	1.1	200	250M 4
47	31.1	10401	1.0	200	250M 4
41	35.9	12012	0.9	200	250M 4
38	38.7	12968	0.8	200	250M 4

Внимание:

Вся представленная мощность относится к механической мощности редукторов.

Для редукторов, помеченных знаком (*) необходимо осуществить проверку предельной термической мощности как указано в разделе 1.6 данного каталога.

IEC	63		71		90		112	
	Y	K	Y	K	Y	K	Y	K
B5	140	154 (Y=140)	140	178 (Y=140)	160	205 (Y=160)	200	252 (Y=200)
	160		160		200		250	
	200		200		250		300	
	250		250		300		350	
B14	120	-	120	-	200	-	-	-
	140	-	140	-	160	-	-	-
	160	-	160	-	-	-	-	-

